

USB-A to Lightning Sync/Charge Coiled Cable, MFi Certified - Black, M/M, USB 2.0, 4 ft. (1.22 m)

MODEL NUMBER: **M100-004COIL-BK**



Charge and sync your latest-generation iPhone, iPad and iPod using the USB-A port on your charger, laptop or desktop computer.

Description

The M100-004COIL-BK USB Sync/Charge Coiled Cable connects your latest-generation iPhone, iPad or iPod to the USB-A port on your USB charger, laptop or desktop computer, so you can charge your Apple device and transfer data at the same time. The cable features a reversible Lightning plug that connects to your Apple device in either direction, ensuring a fast, fumble-free connection.

The M100-004COIL-BK is MFi-certified for use with the latest generation of iPhone, iPad and iPod devices.

This four-foot cord is specially coiled to take up much less space than a normal cable, and has an effective length of 2-ft. (0.61 m) to 3-ft. (0.91 m) when in use. It also resists tangles and knots, making it convenient to store in your car or carry in your purse, backpack or laptop bag. Nickel-plated connectors ensure excellent conductivity, improving performance.

Features

Charge and Sync Your Latest-Generation iPhone, iPad and iPod USB-A male plug connects to charger, laptop or desktop computer's USB port Reversible Lightning male plug connects to Apple devices in either direction for fast, fumble-free connection

MFi-Certified for Device Compatibility Compatible with iPhone, iPad, iPad mini, iPad mini 2, iPad mini 3, iPad mini 4, iPad Air, iPad Air 2, iPad Pro 12.9 inch, iPad Pro 10.5 inch, iPad Pro 9.7 inch and iPod Touch devices with Lightning port

Coiled to Take Up Less Space than Regular Cable Effective length of 2 to 3-ft. (0.61 - 0.91 m) when in use Resists tangles and knots Stores perfectly in car, purse, backpack or laptop bag Nickel-plated connectors for excellent conductivity

Highlights

- MFi-certified for use with iPhone, iPad and iPod devices
- Reversible Lightning plug connects in either direction
- Works with any computer or charger with a USB-A port
- 4 ft. cable is coiled to take up less space
- Effective length of 2-3-ft. (0.61 - 0.91 m) when in use
- Nickel-plated connectors

Applications

- Charge and sync your Apple iPhone, iPad or iPod using the USB-A port on your computer or a wall charger up to 4-ft. (1.22 m) away
- Transfer photos and other important files between an external hard drive and your Apple device

System Requirements

- Device or charger with USB-A port
- Most current iPhone, iPad and iPod devices

Package Includes

- M100-004COIL-BK USB Sync/Charge Coiled Cable with Lightning Connector (M/M), Black, 4-ft. (1.22 m)

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332192110 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--|--------------------------------------|
| Technology | Lightning; USB; USB 2.0 (High Speed) |
| USB Cable Type | Passive |
| INPUT | |
| Maximum Input Amps | 2 |
| POWER | |
| USB Power Delivery (PD) Charging Support | No |
| CHARGING | |
| Total Charging Watts | 12 |
| PHYSICAL | |
| Material of Construction | PU, PVC |
| Color | Black |
| Cable Jacket Color | Black |
| Cable Jacket Material | PVC |
| Cable Jacket Rating | VW-1 |
| Cable Outer Diameter (OD) | 3.8mm |
| Wire Gauge (AWG) | 28/22 |
| Cable Length (ft.) | 4 |
| Cable Length (m) | 1.22 |
| Cable Length (in.) | 48 |
| Shipping Dimensions (hwd / cm) | 11.61 x 6.10 x 2.31 |
| Shipping Dimensions (hwd / in.) | 4.57 x 2.40 x 0.91 |
| Shipping Weight (kg) | 0.02 |
| Shipping Weight (lbs.) | 0.05 |
| Unit Packaging Type | Box |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4 to 140 F (-20 to 60 C) |
| Storage Temperature Range | -4 to 176 F (-20 to 80 C) |
| Operating Humidity Range | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range | 0% to 90% RH, Non-Condensing |
| Power Provided to Connected Device(s) | 12W (5V/2.4A) |
| CONNECTIONS | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--------------------------------------|--------------------------|
| Side A - Connector 1 | USB A (MALE) |
| Side B - Connector 1 | LIGHTNING (MALE) |
| Connector Plating | Nickel |
| Contact Plating | Gold |
| FEATURES & SPECIFICATIONS | |
| Data Transfer Rate | 480 Mbps |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| Angled Plug | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | MFi |
| Product Compliance | RoHS; REACH; UKCA |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>