



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.triplite.com

This Thunderbolt 3 docking station must be connected to a Thunderbolt 3-enabled laptop or computer using a Thunderbolt 3 cable to achieve maximum data transfer and video transmission specifications.

Thunderbolt 3 Dock w USB-C Compatibility, Dual Display - 8K DisplayPort, USB 3.2 Gen 2 10G, USB-A/C Hub, Memory Card, GbE, 60W Charging

MODEL NUMBER: MTB3-DOCK-03



Turns your MacBook Pro or Windows laptop into a 10-port workstation capable of transmitting 8K video.

Features

Thunderbolt 3 Dock Turns Your MacBook Pro into a 10-Port 8K Workstation This Thunderbolt 3 docking station dramatically expands the potential of your MacBook Pro or Windows laptop by adding 10 ports to its Thunderbolt 3 or USB-C MFPD port. Not only does the MTB3-DOCK-03 allow you to transmit 8K video to one display or 4K video to two displays, you can also add USB peripherals, record a podcast, connect to a Gigabit Ethernet network, charge your laptop and more, all at the same time.

Supports DisplayPort Alternate Mode for Transmitting Audio/Video Signals By connecting the included Thunderbolt 3 cable to a source device that supports DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers.

Thunderbolt 3 Supports Blisteringly Fast 40 Gbps Data Transfer Speeds The included Thunderbolt 3 cable supports bidirectional speeds up to 40 Gbps, which is eight times faster than USB 3.0, four times faster than Thunderbolt 1 and twice as fast as Thunderbolt 2. With dual 20 Gbps channels moving data both directions at the same time, the MTB3-DOCK-03 is perfectly suited for 4K video streaming and editing on two monitors, as well as transferring large RAW video or CAD files. When connected to a host computer's USB-C MFPD port, the cable supports 26.2 Gbps speeds.

DisplayPort Multi-Stream Transport (MST) Allows Connection of Multiple Displays By connecting the included Thunderbolt 3 cable to a source that supports DisplayPort MST Mode, you may connect two displays simultaneously (DP & USB-C) at resolutions of 8K (30 Hz) plus 4K (30 Hz) or both displays at 4K (60 Hz). This allows you to display the same image on both monitors, extend your host desktop across both with different windows open on each, or combine both into one large display as a video wall.

Transmits Crystal-Clear 8K and 4K Video for Professional Editing and Digital Signage Both the DisplayPort and Thunderbolt 3 video ports can achieve resolutions up to 8K (7680 x 4320) at 30 Hz, when used with a Thunderbolt 3-enabled source computer and Thunderbolt 3 cable. When used with an MFPD-enabled source computer, the DisplayPort connector's maximum resolution is 4K (3840 x 2160) at 60 Hz. The Thunderbolt 3 port also allows daisy-chaining up to six devices, including RAID memory and other

Highlights

- Connects 2 displays at the same time for multitasking and increasing productivity
- Transmits 8K video (7680 x 4320) @ 30 Hz to a single display for professional users
- Can operate with Thunderbolt 3 or USB-C Multi-Function DisplayPort (MFPD) host
- Supports Thunderbolt 3 speeds up to 40 Gbps between compatible devices
- USB 3.2 Gen 2 data ports allow connection of flash drives and other peripherals

Applications

- Extend or mirror your MacBook Pro or Windows laptop on multiple displays to aid in multitasking and increase productivity
- Edit HDR production video or digital photos using an 8K monitor
- Transfer files from one Thunderbolt 3 device to another at 40 Gbps
- Access a wired Gigabit Ethernet network in a location with no or spotty Wi-Fi
- Connect a microphone/headset to record a podcast or speakers to listen to music

System Requirements

- Source device with Thunderbolt 3 port that supports DisplayPort MST Mode or USB-C port that supports Multi-Function DisplayPort
- Display device with Thunderbolt 3 or DisplayPort input

Package Includes

- MTB3-DOCK-03 Thunderbolt 3 Dock, Dual Display
- Thunderbolt 3 cable (M/M), 1.6 ft.
- External power supply (Input: 100–240V, 50/60 Hz, 3.0A; Output: 20V 6A)
- C13 to NEMA 5-15P Adapter, 4 ft.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

storage devices.

• Owner's manual

USB Ports Connects Keyboards, Thumb Drives and Other USB PeripheralsTwo USB-A hub ports and one USB-C port accept USB peripherals, such as flash drives, mice, keyboards, external hard drives and printers. All three support lightning-fast USB 3.2 Gen 2 data transfer rates up to 10 Gbps and are backward compatible with previous USB generations. The USB-C port supports USB charging up to 5V 1.5A. One USB-A port supports charging speeds up to 5V 1.5A. The other supports charging up to 5V 900mA.

Accesses a Wired Gigabit Ethernet NetworkThe RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

Connects Stereo Audio Equipment for Recording and PlaybackThis Thunderbolt 3 docking station contains one 3.5 mm mini stereo jack, convenient for connecting speakers, headphones or a microphone to your workstation. You can listen to music or record the latest episode of your podcast.

Allows External Memory AccessThe memory card slots support Micro SD and SD cards for transferring data to and from your connected computer or laptop. Both slots may be used at the same time.

Included Thunderbolt 3 Cable Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible Thunderbolt 3 male connector plugs into its port in either direction for an instant connection every time.

Ready to Use Right from the Package, So You Can Plug and Play ImmediatelyThe plug-and-play Thunderbolt 3 dock is specifically designed for use with the MacBook Pro or Windows laptop equipped with a Thunderbolt 3 port. It requires no extra software to be downloaded and installed. Simply plug the included power adapter into a standard AC outlet, and connect the included Thunderbolt 3 cable to your computer's Thunderbolt 3 or USB-C MFDP port.

Specifications

OVERVIEW	
UPC Code	037332250322
Product Type	Docking Station
Technology	DisplayPort; Thunderbolt
Host Connector	THUNDERBOLT 3 (Type-C MALE)
VIDEO	
Number of Monitors Supported	2
Video Ports	THUNDERBOLT 3 (Type-C FEMALE); DISPLAYPORT (FEMALE)
Video Ports Details	DisplayPort 1.4; Thunderbolt 3
Resolutions Supported	Thunderbolt 3: 8K 30Hz (7680 x 4320) DisplayPort: 8K 30Hz (7680 x 4320)
Max Supported Video Resolution	7680 x 4320 (8K) @ 30 Hz (Thunderbolt 3); 3840 x 2160 (4K x 2K) @ 60 Hz (MFDP)
Extended Mode	Yes
Extended Mode Details	For Thunderbolt 3 Source: 1x DP (8K 30Hz) + 1x ThunderBolt 3 (4K 30Hz) via USB-C to C or USB-C to DP or USB-C to HDMI cable or adapter For USB-C MFDP Source: 1x DP (4K 60Hz) + 1x ThunderBolt 3 (4K 60Hz) via USB-C to C or USB-C to DP or USB-C to HDMI cable or adapter



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Mirror Mode	Yes
Mirror Mode Details	For Thunderbolt 3 Source: 1x DP (8K 30Hz) + 1x ThunderBolt 3 (4K 30Hz) via USB-C to C or USB-C to DP or USB-C to HDMI cable or adapter For USB-C MFD Source: 1x DP (4K 60Hz) + 1x ThunderBolt 3 (4K 60Hz) via USB-C to C or USB-C to DP or USB-C to HDMI cable or adapter
Max Supported Color Depth	48-bit Deep Color
HDR Support	Yes
Chroma Sub Sampling	4:4:4
AUDIO	
Audio Ports	3.5MM (FEMALE)
Audio Ports Details	3.5mm Combo Stereo Audio / Microphone Jack
Audio Specification	Supports 8/16/22.05/24/32/44.1/48/96/176.4/192/384 KHz
DATA	
Data Ports	(1) THUNDERBOLT 3 (Type-C FEMALE); (2) USB A (FEMALE); (1) USB C (FEMALE)
Data Ports Details	(2) USB-A - USB 3.2 Gen 2 (10 Gbps); (1) USB-C - ThunderBolt 3 (40 Gbps); (1) USB-C - USB 3.2 Gen 2 (10 Gbps)
NETWORK	
Network Ports	RJ45 (FEMALE)
STORAGE	
Card Slots	SD (FEMALE); MICRO SD (FEMALE)
Card Slots Details	SD 4.0 and Micro SD 4.0Both card readers can be used at the same time
INPUT	
Maximum Input Amps	3.0
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
Bus Powered	No
BATTERY	
Battery Charging (5V/1.5A Port)	Yes
POWER	
AC Adapter	Input: 100–240V, 50/60 Hz, 3.0A; Output: 20V, 6A
External Power Supply Input Specs (V / Hz / A)	100-240V, 50/60Hz, 3.0A
External Power Supply Output Specs (V / A)	20V / 6A
External Power Supply Cord Length (ft.)	4



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

External Power Supply Cord Length (m.)	1.2
DC Barrel Plug	OD: 4.5 x 0.6 x 10.5mm, Positive Pin, Negative Sleeve
USB Power Delivery (PD) Charging Support	Yes
External Power Supply Plug(s)	NEMA 5-15P North America
USB Power Delivery (PD) Charging Specification	60W
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Green (Power), Orange (Transmitting Data)
CHARGING	
Total Charging Watts	60
Charging Ports	Supports 60W (20V 3A) Power to Host Computer; USB-A: 5V 1.5A (7.5W)
Charging Ports / Amps	1.5A; 3A
PHYSICAL	
Material of Construction	PC, ABS, Aluminum
Color	Black; Gray
Shipping Dimensions (hwd / in.)	2.44 x 9.72 x 6.85
Shipping Weight (kg)	0.38
Unit Dimensions (hwd / in.)	0.69 x 3.15 x 5.83
Unit Dimensions (hwd / cm)	1.7 x 8.0 x 14.8
Unit Dimensions (hwd / mm)	17.5 x 80 x 148
Unit Packaging Type	Box
Unit Weight (lbs.)	0.5952
Unit Weight (kg)	0.27
ENVIRONMENTAL	
Operating Temperature Range	32 to 113°F (0 to 45°C)
Storage Temperature Range	32 to 158°F (0 to 70°C)
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5 to 90% RH, Non-condensing
Power Provided to Connected Device(s)	USB-A 5V/1.5A (7.5W); USB-C 20V/3A (60W) to Host Computer
COMMUNICATIONS	
Network Compatibility	1 Gbps (Gigabit)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

CONNECTIONS	
Number of Ports	10
Dock Connectors	DisplayPort, (2) TB3 USB-C, USB-C, RJ45, MICRO SD, SD, 3.5MM, (2) USB-A 3.0
Side A - Connector 1	(2) THUNDERBOLT 3 (Type-C FEMALE)
Side A - Connector 2	DISPLAYPORT (FEMALE)
Side A - Connector 3	RJ45 (FEMALE)
Side A - Connector 4	THUNDERBOLT 3 (Type-C MALE)
Side B - Connector 2	MICRO SD (FEMALE); SD (FEMALE)
Side B - Connector 3	3.5MM (FEMALE)
Side B - Connector 4	(2) USB A (FEMALE); USB C (FEMALE)
Connector Plating	Nickel
Side A - Connector 5	USB A (FEMALE)
FEATURES & SPECIFICATIONS	
Displayport Specification	1.4
HDCP Specification	1.4; 2.2
USB Hub Ports	Yes
Number of USB Hub Ports	3
USB Specification	USB 3.2 Gen 2 (Up to 10 Gbps)
Driver Required	No
Recommended Category Cable	Cat5/Cat5e/Cat6 Cables
UASP Support	No
Auto MDIX Support	No
Full Duplex Support	Yes
Suspend Mode Support	No
Remote Wakeup Support	No
SD Card Specification	SD; Micro SD
Thunderbolt Specification	Thunderbolt 3 (up to 40Gbps short or active cables)
STANDARDS & COMPLIANCE	
External Power Supply Certifications	CCC; CE; GS; PSE; TUV; UL; cUL
Product Compliance	RoHS; REACH; FCC (USA)
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<https://www.tripplite.com/products/product-certification-agencies>