

The N050-P12 is designed specifically to be used in PoE applications. It does not add PoE power to a Cat5e signal not already transmitting both data and power.

Cat5e Wall-Mount 12-Port Patch Panel - PoE+ Compliant, 110/Krone, 568A/B, RJ45 Ethernet, TAA

MODEL NUMBER: **N050-P12**



PoE+-compliant 12-port patch panel manages and organizes Cat5e data/power cable connections in your high-density network.

Description

IEC 60512-99-002 Compliant
 PoE Certificate Number: 2019-248
 110/Krone Dual IDC
 UTP Cat6a 22-24 AWG solid cable (Requires PoE cable if used in PoE setting)

Features

12-Port Patch Panel Manages and Organizes High-Density Cat5e Network Cabling This patch panel enables quick, easy cable patching. Just plug Cat5e patch cables into its 12 front RJ45 ports, and use a 110 or Krone punch-down tool (do not use a 4/5 pair 110 punch-down tool) to terminate color-coded connections in the rear. Both the RJ45 ports and punchdown terminals are clearly numbered, and the front ports have blank labels to help you identify individual cable runs. The N050-P12 supports EIA/TIA 568A and 568B wiring standards and is compatible with all network applications.

Specifically Designed for Use in Power over Ethernet Plus (PoE+) Applications This Power over Ethernet patch panel maximizes performance with PoE+ applications. It prevents spark-gap erosion that degrades the plug and jack contacts over time and can affect data and/or power transmission capabilities. The N050-P12 is designed to handle the frequent mating and unmating of surveillance cameras, VoIP phone systems, wireless access points and other PoE and PoE+ devices under electrical load.

Effortlessly Mounts to a Wall or Desk Using the Included Frame The 12-port patch panel is constructed from aluminum with a plastic 89B frame that mounts to a wall, desk or similar flat surface. The patch panel easily snaps into and out of the frame, allowing you to remove it to make new 110 connections and snap it back into place. Included cable ties help organize your connections and cut down on cord clutter.

TAA-Compliant for GSA Schedule Purchases The N050-P12 is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Highlights

- Power over Ethernet patch panel prevents spark-gap erosion that can affect transmission
- 12 RJ45 and 110 ports numbered/labeled/color-coded for immediate cable identification
- Durable aluminum panel with ABS plastic frame that mounts easily to wall or desk
- Supports EIA/TIA 568A/B wiring standards for either 110 or Krone-type terminations
- Ideal for managing Cat5e cable patching in high-density IT environments

Applications

- Patch cables to PoE+ devices mounted in areas that are difficult to reach or have no electrical outlets
- Add routers, switches, wireless access points, security cameras, sensors and other PoE+ devices to an Ethernet network configuration

Package Includes

- N050-P12 12-Port Wall-Mount Cat5e Patch Panel - PoE+ Compliant
- (4) Cable ties
- Installation instructions



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Lifetime Warranty The N050-P12 is backed by a lifetime warranty, ensuring reliability and performance.

Specifications

| OVERVIEW | |
|-------------------------------------|---------------------------------------|
| UPC Code | 037332210395 |
| Product Type | Punchdown |
| Technology | Cat5/5e |
| PHYSICAL | |
| Color | Black |
| Shipping Dimensions (hwd / cm) | 5.08 x 27.18 x 8.38 |
| Shipping Dimensions (hwd / in.) | 2.00 x 10.70 x 3.30 |
| Shipping Weight (kg) | 0.32 |
| Shipping Weight (lbs.) | 0.70 |
| Unit Dimensions (hwd / in.) | 2.24 x 10.04 x 1.88 |
| Unit Dimensions (hwd / cm) | 5.70 x 25.5 x 4.77 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 14 to 140 F (-10 to 60 C) |
| Storage Temperature Range | -40 to 154.4 F (-40 to 68 C) |
| Relative Humidity | 10% to 90% RH, Non-Condensing |
| CONNECTIONS | |
| Number of Ports | 12 |
| PoE Power Budget (Watts) | 90 |
| Side A - Connector 1 | 110 IDC |
| Side B - Connector 1 | RJ45 (FEMALE) |
| PoE Type | Type 3 PoE++/UPoE (60W, IEEE 802.3bt) |
| STANDARDS & COMPLIANCE | |
| Product Certifications | UL Listed |
| Product Compliance | RoHS; CE (Europe) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<https://www.tripplite.com/products/product-certification-agencies>