



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## Up-Angle Cat6 Gigabit Molded UTP Ethernet Cable (RJ45 Right-Angle Up M to RJ45 M), Blue, 10 ft. (3.05 m)

MODEL NUMBER: N204-010-BL-UP



### Highlights

- Space saving design
- Up Angle connector to Straight
- Cat6 Gigabit rated

### System Requirements

- Use with Cat6, Cat5e, Cat5, or VoIP networks

### Package Includes

10-ft. (3.05 m) Blue Cat6 Up Angle to Straight RJ45 - RJ45 Patch cable

### Features

- 10-ft. (3.05 m) Blue Cat6, Up Angle to Straight RJ45 - RJ45 Patch cable
- PVC 4 Pair Stranded Conductors, 24AWG
- Fully Molded Ends
- ETL Verified to TIA/EIA -568-B
- 550Mhz Gigabit Speed Rated

## Specifications

| OVERVIEW                  |                 |
|---------------------------|-----------------|
| UPC Code                  | 037332167613    |
| Technology                | Cat6            |
| PHYSICAL                  |                 |
| Cable Jacket Color        | Blue            |
| Cable Jacket Material     | PVC             |
| Cable Jacket Rating       | CM              |
| Cable Shielding           | UTP             |
| Cable Outer Diameter (OD) | 6.0mm           |
| Number of Conductors      | 4 Pair          |
| Conductor Material        | Stranded Copper |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Conductor Gauge                      | 24 AWG                              |
| Cable Length (ft.)                   | 10                                  |
| Cable Length (m)                     | 3.05                                |
| Cable Length (in.)                   | 120                                 |
| Cable Length (cm)                    | 304.8                               |
| Shipping Dimensions (hwd / cm)       | 1.27 x 16.51 x 17.02                |
| Shipping Dimensions (hwd / in.)      | 0.50 x 6.50 x 6.70                  |
| Shipping Weight (kg)                 | 0.14                                |
| Shipping Weight (lbs.)               | 0.30                                |
| <b>ENVIRONMENTAL</b>                 |                                     |
| Operating Temperature Range          | 14 to 122 F (-10 to 50 C)           |
| Storage Temperature Range            | 5 to 140 F (-15 to 60 C)            |
| Operating Humidity Range             | 0% to 90% RH, Non-Condensing        |
| Storage Humidity Range               | 0% to 90% RH, Non-Condensing        |
| <b>COMMUNICATIONS</b>                |                                     |
| Bandwidth per TIA Standard           | 250 MHz                             |
| Maximum Bandwidth as Tested          | 500 MHz                             |
| Network Compatibility                | 1 Gbps (Gigabit)                    |
| IEEE Standards Supported             | 802.3an                             |
| <b>CONNECTIONS</b>                   |                                     |
| Side A - Connector 1                 | RJ45 (MALE)                         |
| Side B - Connector 1                 | RJ45 (MALE) - UP ANGLE              |
| Crossover Wiring                     | No                                  |
| Contact Plating                      | Gold                                |
| Connector Type                       | Molded                              |
| Wiring Configuration                 | EIA/TIA 568B                        |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                     |
| IP68 Rated                           | No                                  |
| Snagless Connector                   | No                                  |
| Antibacterial                        | No                                  |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                     |
| Product Compliance                   | RoHS; IEEE 802.3an 10GBase-T; REACH |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| WARRANTY                            |                           |
|-------------------------------------|---------------------------|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>