

## Heavy-Duty PDU Power Cord, C13 to Left-Angle C14 - 15A, 250V, 14 AWG, 6 ft. (1.83 m), Black

MODEL NUMBER: P005-006-14LA



Computer power extension cord with left-angle C14 plug allows connection of a PC, printer or monitor in tight spaces or awkward angles.

### Features

**C14-to-C13 Power Cable for Network Devices That Require a Heavy-Gauge Connection** This IEC-320-C14 to IEC-320-C13 cable features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This C14 male to C13 female cord can be used to connect a computer, server, monitor or drive to a UPS system or PDU or replace or upgrade the standard power cord provided by the device's manufacturer. The 6-ft. (1.83 m) length allows you flexibility in placing equipment with respect to the power outlet.

**Left-Angle C14 Plug Makes Connecting in Tight Spaces Easier** The C13 to C14 left-angle cable is easier to install in confined spaces, such as the back of a rack enclosure cabinet. When plugged in, the left-angled C14 plug guides the computer power supply cable parallel to your peripheral, allowing you to push the device up against a wall or hide it behind a desk to maximize space.

### Highlights

- Left-angle C14 plug allows easier connection in confined or hard-to-reach spaces
- Recommended for powering computers, servers and other network devices
- 6-ft. (1.83 m) length allows flexibility in placing devices in relationship to AC outlet
- PDU-style cord replaces or upgrades standard power cord provided by manufacturer
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

### Applications

- Connect devices like computers, servers and monitors to a PDU up to 6-ft. (1.83 m) away in your data center
- Extend an existing power connection up to 6-ft. (1.83 m) to more easily place a device or reach a power source away from your workstation
- Update or replace the standard power cord provided by a device's original manufacturer
- Power a device located in a hard-to-access area behind a desk or flush against a wall

### Package Includes

- P005-006-14LA C13 to Left-Angle C14 Power Cable, 6-ft. (1.83 m), Black

## Specifications

| OVERVIEW                    |                                                                           |
|-----------------------------|---------------------------------------------------------------------------|
| UPC Code                    | 037332179920                                                              |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Server; Router; Network Switch; UPS; PDU |
| Country/Region              | Global                                                                    |
| INPUT                       |                                                                           |
| Maximum Input Amps          | 15                                                                        |
| Voltage Compatibility (VAC) | 100-250                                                                   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| PHYSICAL                           |                                     |
|------------------------------------|-------------------------------------|
| Plug Color                         | Black                               |
| Cable Jacket Color                 | Black                               |
| Cable Jacket Material              | PVC                                 |
| Cable Jacket Rating                | FT2                                 |
| Power Cord Jacket Type             | SJT                                 |
| Cable Outer Diameter (OD)          | 9.2mm                               |
| Number of Conductors               | 3                                   |
| Wire Gauge (AWG)                   | 14                                  |
| Wire Gauge (OD - mm <sup>2</sup> ) | 2.08                                |
| Cable Length (ft.)                 | 6                                   |
| Cable Length (m)                   | 1.83                                |
| Shipping Dimensions (hwd / cm)     | 25.40 x 17.78 x 0.25                |
| Shipping Dimensions (hwd / in.)    | 10.00 x 7.00 x 0.10                 |
| Shipping Weight (kg)               | 0.30                                |
| Shipping Weight (lbs.)             | 0.66                                |
| ENVIRONMENTAL                      |                                     |
| Operating Temperature Range        | -4 TO 140 F (- 20° TO 60°C)         |
| Storage Temperature Range          | -4 TO 140 F (- 20° TO 60°C)         |
| Operating Humidity Range           | 20-80% RH                           |
| Storage Humidity Range             | 20-80% RH                           |
| CONNECTIONS                        |                                     |
| Side A - Connector 1               | IEC-320-C14 - LEFT ANGLE            |
| Side B - Connector 1               | IEC-320-C13                         |
| FEATURES & SPECIFICATIONS          |                                     |
| High Voltage                       | Yes                                 |
| Locking Plug                       | No                                  |
| Angled Plug                        | Yes                                 |
| STANDARDS & COMPLIANCE             |                                     |
| Product Certifications             | CSA (Canada); cUL Listed; UL Listed |
| Product Compliance                 | RoHS; REACH                         |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| WARRANTY                            |                           |
|-------------------------------------|---------------------------|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>