

Desktop Computer AC Power Cord, Right-Angle NEMA 5-15P to C13 - 10A, 125V, 18 AWG, 15 ft. (4.57 m), Black

MODEL NUMBER: P006-015-15D











Computer power cable allows you to connect your PC, printer or monitor into a surge protector, PDU or UPS with a NEMA 5-15R outlet.

Features

Desktop Computer Power Cord Connects PCs, Printers, Monitors and Other EquipmentThis computer power supply cable is designed for home/office desktop computer applications. You can use it to connect a computer, monitor, printer, scanner or other device with a C14 power inlet to an AC wall outlet, surge protector, UPS system or PDU. The 15-ft. (4.57 m) length allows you great flexibility in placing equipment with respect to the power outlet. Note: This cord is not for use in European markets.

Right-Angle PC Power Cable Is Easier to Connect in Tight SpacesThe angled NEMA 5-15P connector makes installations easier in confined spaces, such as the back of a rack enclosure cabinet. When plugged in, the right-angle plug guides the computer power supply cable parallel to the wall, allowing you to push furniture up against a wall to maximize space.

Highlights

- Right-angle 5-15P plug allows easier connection in confined or hard-to-reach spaces
- Recommended for powering computers, printers and other home/office peripherals
- 15-ft. (4.57 m) length allows great flexibility in placing devices in relationship to AC outlet
- Ideal replacement for worn-out or missing computer power
- NEMA 5-15P plug connects to AC power; C13 plug connects to device's C14 inlet

Applications

- Connect devices like computers, monitors, scanners and printers to a power outlet up to 15-ft. (4.57 m) away in your home office, work space or dorm room
- Extend an existing power connection up to 15-ft. (4.57 m) to more easily place a device or reach a power source away from your workstation
- Provide a high-quality replacement for a worn-out or missing power cord
- Power a device located in a hard-to-access area behind a desk or flush against a wall

Package Includes

 P006-015-15D Right-Angle NEMA 5-15P to C13 Computer Power Cable, 15-ft. (4.57 m), Black

Specifications

OVERVIEW		
UPC Code	037332241900	
Device Compatibility	Computer; Monitor/HDTV; Printer; Server; UPS; PDU	
Country/Region	North America	
INPUT		
Maximum Input Amps	10	



Voltage Compatibility (VAC)	125
PHYSICAL	
Plug Color	Black
Cable Jacket Color	Black
Cable Jacket Material	PVC
Cable Jacket Rating	FT2
Power Cord Jacket Type	SJT
Cable Outer Diameter (OD)	7.7mm
Number of Conductors	3
Wire Gauge (AWG)	18
Wire Gauge (OD - mm²)	0.82
Cable Length (ft.)	15
Cable Length (m)	4.57
Shipping Dimensions (hwd / in.)	1.00 x 11.50 x 14.00
Shipping Weight (kg)	0.45
Shipping Weight (kg) ENVIRONMENTAL	0.45
	-4 TO 140 F (- 20° TO 60°C)
ENVIRONMENTAL	
ENVIRONMENTAL Operating Temperature Range	-4 TO 140 F (- 20° TO 60°C)
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C)
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH 20-80% RH
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1 Side B - Connector 1	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH 20-80% RH NEMA 5-15P - RIGHT ANGLE
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1 Side B - Connector 1	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH 20-80% RH NEMA 5-15P - RIGHT ANGLE
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1 Side B - Connector 1 FEATURES & SPECIFICATIONS High Voltage	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH 20-80% RH NEMA 5-15P - RIGHT ANGLE IEC-320-C13
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1 Side B - Connector 1 FEATURES & SPECIFICATIONS High Voltage Locking Plug	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH 20-80% RH NEMA 5-15P - RIGHT ANGLE IEC-320-C13
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1 Side B - Connector 1 FEATURES & SPECIFICATIONS High Voltage Locking Plug Angled Plug	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH 20-80% RH NEMA 5-15P - RIGHT ANGLE IEC-320-C13
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1 Side B - Connector 1 FEATURES & SPECIFICATIONS High Voltage Locking Plug Angled Plug STANDARDS & COMPLIANCE	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH 20-80% RH NEMA 5-15P - RIGHT ANGLE IEC-320-C13 No No Yes
ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1 Side B - Connector 1 FEATURES & SPECIFICATIONS High Voltage Locking Plug	-4 TO 140 F (- 20° TO 60°C) -4 TO 140 F (- 20° TO 60°C) 20-80% RH 20-80% RH NEMA 5-15P - RIGHT ANGLE IEC-320-C13



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Product Warranty Period (Worldwide)	Lifetime limited warranty
-------------------------------------	---------------------------

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies