

AT Serial Modem Gold Cable (DB25 to DB9 M/F), 6 ft. (1.83 m)

MODEL NUMBER: P404-006



Highlights

- Superior molded cables with foilshielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Use to connect your computers serial port to an external modem

System Requirements

- Hayes compatible external modem with a Female DB25 port.
- Computer with an available DB9 Male serial port

Package Includes

• 6-ft. (1.83 m) Serial Modem Cable DB9F/25M

Description

6-ft. (1.83 m) serial modem cable. DB25M to DB9F. Superior molded cables with built-in strain relief ensures the cable will last a very long time. Foil-shielding provide maximum EMI/RFI protection. Gold plated connectors and gold plated copper contacts offer superior conductivity.

Features

- Superior molded cables with built-in strain relief ensures cable will last a very long time
- Foil-shielding provide maximum EMI/RFI protection
- Gold plated connectors and gold plated copper contacts offer superior conductivity

Specifications

OVERVIEW	
UPC Code	037332012197
PHYSICAL	
Color	Black
Cable Jacket Color	Black
Cable Length (ft.)	6
Cable Length (m)	1.83
Shipping Dimensions (hwd / cm)	1.27 x 11.68 x 19.81
Shipping Dimensions (hwd / in.)	0.50 x 4.60 x 7.80
Shipping Weight (kg)	0.18



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

0.40	
CONNECTIONS	
DB9 (FEMALE)	
DB25 (MALE)	
FEATURES & SPECIFICATIONS	
No	
No	
STANDARDS & COMPLIANCE	
RoHS	
WARRANTY	
Lifetime limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies