

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA

Telephone: 773.869.1234 www.tripplite.com

4K HDMI Fiber Active Optical Cable (AOC) - 4K 60 Hz, HDR, 4:4:4 (M/M), 50 m

MODEL NUMBER: P568-50M-FBR





Fiber HDMI cable creates crystal-clear 4K video/audio connections with 4:4:4 color for home theaters and digital signage.

Features

4K HDMI Cable Connects Home Theater, Gaming & Digital Signage Components

This 4K HDMI cable securely connects HDMI-enabled laptops, tablets, PCs, Blu-ray players, game consoles or satellite/cable TV boxes to HDTVs, HD monitors, projectors or home theater receivers. Because the cable uses optical fiber, it can transmit HDMI signals longer distances with no latency or loss. It also eliminates any EMI/RFI line noise that can interfere with your audio/video signal and disrupt the performance of your connected equipment.

Enjoy the Clarity of 4K HDMI Video with Multi-Channel Audio, HDR and 4:4:4 Color

This HDMI cable supports Ultra HD video resolutions up to 4K for crystal-clear picture and sound. High Dynamic Range (HDR) provides a wide range of vibrant colors with richer contrast, brighter whites and deeper blacks that pop on your 4K display. It also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor, as well as 3D, 48-bit Deep Color, DTS-HD Master Audio and Dolby True HD.

Advanced Fiber Cable Is Easier to Install than Copper

Because the fiber cable is slimmer and more flexible than standard copper HDMI cables, the P568-50M-FBR is easier to install around corners and in hard-to-reach spaces behind equipment. It draws power from the connected device, so no external power supply is needed to transmit the HDMI signal across the longer distances unique to fiber optic cabling. **Note**: The cable must be installed in the correct direction to function properly, so check the Source and Display labels on the connectors before installation.

Highlights

- Supports UHD resolutions up to 4K (4:4:4) for crystal-clear video
- Carries High Dynamic Range (HDR) signals for rich contrast and expanded color accuracy
- Fiber optic strands transmit audio/video over longer distances than standard copper
- Dispels EMI/RFI line noise that can disrupt A/V signal and affect equipment performance
- Plug-and-play cable draws power from connected device for easy, immediate installation

Applications

- Watch 4K video content from a Blu-ray player, game console, laptop or tablet on an Ultra HD television, monitor or projector
- Connect a Chromebook or MacBook to a conference table's A/V box to give a video presentation on a large screen
- Send Ultra HD content to digital signs or point-of-sale displays
- Connect security cameras and other A/V surveillance equipment to a central display

Package Includes

 P568-50M-FBR High-Speed HDMI Fiber Active Optical Cable, M/M, Black, 50 m (164 ft.)

Specifications

OVERVIEW		
UPC Code	037332236876	
Product Type	Active	
Technology	номі	





VIDEO		
Video Input	HDMI (MALE)	
Video Output	HDMI (MALE)	
Max Supported Video Resolution	3840 x 2160 @ 60Hz	
Max 1280 x 720 (720p) Range (ft)	164	
Max 1920 x 1080 (1080p) Range (ft)	164	
Max 1920 x 1200 Range (ft)	164	
Max 2560 x 1600 Range (ft)	164	
Max 3840 x 2160 (4K@30Hz) Range (ft)	164	
Max 3840 x 2160 (4K@60Hz) Range (ft)	164	
Max Supported Color Depth	48-bit Deep Color	
HDR Support	Yes	
3D Video Supported	Yes	
Chroma Sub Sampling	4:4:4	
Maximum Signal Range (ft)	164	
Maximum Signal Range (m)	50	
EDID Support	Yes	
Signal Transmission	Bidirectional	
AUDIO		
Audio Specification	Stereo Audio	
INPUT		
Bus Powered	No	
POWER		
Power Over Cable (PoC) Support	No	
USER INTERFACE, ALERTS & CON	TROLS	
LED Indicators	0	
PHYSICAL		
Color	Black	
Cable Jacket Color	Black	
Connector Color	Silver	
Cable Jacket Material	PVC	





Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	4.8mm	
Wire Gauge (AWG)	30	
Cable Length (ft.)	164	
Cable Length (m)	50.00	
Ferrite Core	No	
Minimum Bend Radius	48mm	
Number of Displays	1	
Form Factor/Mounting Options	Cable	
Shipping Dimensions (hwd / in.)	3.45 x 6.50 x 6.50	
Shipping Weight (kg)	1.72	
Shipping Weight (lbs.)	3.80	
ENVIRONMENTAL		
Operating Temperature Range	32 TO 113 F (0 TO 45 C)	
Storage Temperature Range	-40 - 80 °C (-40 - 176 °F)	
Operating Humidity Range	10 to 85% RH, Non-Condensing	
Storage Humidity Range	5 to 90% RH, Non-Condensing	
COMMUNICATIONS		
EDID Compatible	No	
IR Remote Extension Support	No	
RS-232 Serial Extension Support	No	
Consumer Electronics Control (CEC) Supported	Yes	
USB Extension Support	No	
CONNECTIONS		
Side A - Connector 1	HDMI (MALE)	
Side B - Connector 1	HDMI (MALE)	
Connector Plating	Gold	
Contact Plating	Gold	
Connector Style	Straight	
Latching or Gripping Connector	No	
FEATURES & SPECIFICATIONS		
HDCP Specification	2.2; 1.4	
·		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Driver Required	No	
EMI/RFI Line Noise Protection	No	
10/100 Ethernet Extension Support	No	
MST Support	No	
IP68 Rated	No	
Built-In Equalizer	No	
Antibacterial	No	
Armored Cable	No	
Ethernet Support	Yes	
IP20 Rated	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies