

High-Speed HDMI Extension Cable with Ethernet and Digital Video with Audio, Ultra HD 4K (M/F), 6 ft. (1.83 m)

MODEL NUMBER: P569-006-MF





Extends the length of an existing high-speed HDMI cable connecting Ethernet or digital audio/video to a 4K television set, projector or monitor.

Features

Connects HDMI Source to 4K TV, Projector or Monitor

- Extends existing Ethernet and digital audio/video connections between HDMI source and display
- Ideal for connecting an iPad, Blu-ray player or video game system to an HDTV or other HDMI display

High Performance and Wide Compatibility

- Supports UHD video resolutions up to 4K and 3D
- Supports audio return channel to simplify setups between displays and A/V receivers
- Backward compatible with previous HDMI generations

Superior Quality Ensures a Flawless Signal

- Corrosion-resistant gold-plated connectors for optimal signal transfer
- Fully molded construction with strain relief for durability and long life
- Flexible PVC jacket easy to install in tight spaces

Specifications

OVERVIEW	
UPC Code	037332191571
Product Type	Passive
Technology	HDMI

Highlights

- Supports UHD video resolutions up to 4K
- Supports Ethernet data connectivity
- Backward compatible with previous HDMI generations
- Perfect for video-mirroring your iPad® to an HDTV

System Requirements

 Existing high-speed HDMI with Ethernet M/M cable

Package Includes

 P569-006-MF High-Speed HDMI Extension Cable (M/F), 6 ft.



VIDEO		
Max Supported Video Resolution	3840 x 2160 @ 30Hz	
Max Supported Color Depth	24-bit True Color	
HDR Support	No	
3D Video Supported	Yes	
Chroma Sub Sampling	4:4:4	
EDID Support	Yes	
Signal Transmission	Bidirectional	
AUDIO		
Audio Specification	Stereo Audio	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	0	
PHYSICAL		
Color	Black	
Cable Jacket Color	Black	
Connector Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	6mm	
Wire Gauge (AWG)	30	
Cable Length (ft.)	6	
Cable Length (m)	1.83	
Ferrite Core	No	
Minimum Bend Radius	60mm	
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27	
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50	
Shipping Weight (kg)	0.11	
Shipping Weight (lbs.)	0.24	
ENVIRONMENTAL		
Operating Temperature Range	32 TO 113 F (0 TO 45 C)	
Storage Temperature Range	-40 - 80 °C (-40 - 176 °F)	
Operating Humidity Range	10 to 85% RH, Non-Condensing	





Storage Humidity Range	5 to 90% RH, Non-Condensing	
COMMUNICATIONS		
Consumer Electronics Control (CEC) Supported	Yes	
CONNECTIONS		
Side A - Connector 1	HDMI (MALE)	
Side B - Connector 1	HDMI (FEMALE)	
Connector Plating	Gold	
Contact Plating	Gold	
Connector Style	Straight	
Latching or Gripping Connector	No	
FEATURES & SPECIFICATIONS		
HDCP Specification	1.4	
EMI/RFI Line Noise Protection	No	
MST Support	No	
IP68 Rated	No	
Antibacterial	No	
Armored Cable	No	
Ethernet Support	Yes	
IP20 Rated	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies