

DisplayPort Cable with Latching Connectors, 4K 60 Hz (M/M), Black, 10 ft. (3.05 m)

MODEL NUMBER: P580-010









Highlights

- Digital Video and Audio in one cable
- Small footprint compared to VGA or DVI
- Supports Ultra High Definition (UHD) 4K x 2K video resolutions up to 3840 x 2160 @ 60Hz, including 1080p

Package Includes

 DisplayPort to DisplayPort Cable 4K with Latches (M/M), 10 ft.

Features

- The future standard for Digital Video and Audio connections
- Supports Displayport v1.2
- Supports High Definition Content Protection (HDCP)
- Supports Ultra High Definition (UHD) 4K x 2K video resolutions up to 3840 x 2160 @ 60Hz, including 1080p

Specifications

OVERVIEW		
UPC Code	037332145956	
Product Type	Passive	
Technology	DisplayPort	
VIDEO		
Max Supported Video Resolution	3840 x 2160 @ 60Hz	
Max Supported Color Depth	24-bit True Color	
HDR Support	No	
3D Video Supported	Yes	
Chroma Sub Sampling	4:2:0; 4:2:2	
Signal Transmission	Bidirectional	



PHYSICAL		
Color	Black	
Cable Jacket Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	6.0MM	
Wire Gauge (AWG)	30	
Cable Length (ft.)	10	
Cable Length (m)	3.05	
Ferrite Core	No	
Minimum Bend Radius	60mm	
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27	
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50	
Shipping Weight (kg)	0.16	
Shipping Weight (lbs.)	0.35	
ENVIRONMENTAL		
Operating Temperature Range	32 TO 113 F (0 TO 45 C)	
Storage Temperature Range	-40 to 158 F (-40 to 70 C)	
Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 90% RH, Non-Condensing	
COMMUNICATIONS		
EDID Compatible	Yes	
Consumer Electronics Control (CEC) Supported	No	
CONNECTIONS		
Side A - Connector 1	DISPLAYPORT (MALE)	
Side B - Connector 1	DISPLAYPORT (MALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
Connector Style	Straight	
Latching or Gripping Connector	Yes	
FEATURES & SPECIFICATIONS		
Displayport Specification	1.2	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

HDCP Specification	2.2	
EMI/RFI Line Noise Protection	No	
MST Support	Yes	
IP68 Rated	No	
Antibacterial	No	
Armored Cable	No	
Ethernet Support	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH; WEEE	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies