

Mini DisplayPort 1.2a to HDMI Active Adapter Cable (M/M), 4K 60 Hz, HDCP 2.2, 12 ft. (3.7 m)

MODEL NUMBER: P586-012-HD-V2A











HDCP 2.2-compliant cable connects the Mini DisplayPort (mDP) or Thunderbolt port on your PC, Mac or tablet to a 4K-enabled HDMI monitor, projector or television.

Features

Send UHD Mini DisplayPort 1.2a Signals to a 4K HDMI DisplayConnects mDP or Thunderbolt PC, Mac or tablet to a 4K-enabled HDMI monitor, projector or HDTVRecommended for displaying video on a large monitor or digital signmDP and high-grip HDMI male connectorsNo separate power adapter required

Vibrant Video QualitySupports UHD video resolutions up to 4K @ 60 Hz (3840 x 2160) as specified in HDMI 2.0Supports HDCP 2.2, audio and EDIDActive adapter compatible with Single-Mode and Dual-Mode (DP++) DisplayPort outputRecommended for graphics cards, such as AMD Eyefinity, that don't output DP++ signals

Superior Materials for Superior PerformanceGold-plated HDMI connector and contacts for maximum conductivity and minimum data lossSpecial high-grip HDMI plug prevents accidental disconnectionsIntegral strain relief provides cable and connectors with flexibility and reduces stress

Specifications

OVERVIEW		
UPC Code	037332200624	
Product Type	Active Cable	
Technology	HDMI; DisplayPort	
VIDEO		
Max Supported Video Resolution	4K @ 60 Hz (3840 x 2160)	
Max Supported Color Depth	8-bit	
HDR Support	Yes	

Highlights

- Supports video resolutions up to 4K @ 60 Hz (3840 x 2160)
- Compliant with latest HDCP 2.2 standards
- No separate power adapter required
- High-grip HDMI plug prevents accidental disconnections
- Supports EDID specifications

Package Includes

 P586-012-HD-V2A Mini DisplayPort 1.2a to HDMI Active Adapter Cable (M/M), 12 ft.





PHYSICAL		
Material of Construction	ABS, PVC	
Color	Black	
Cable Jacket Color	Black	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	5.0 +/- 15mm	
Wire Gauge (AWG)	32	
Cable Length (ft.)	12	
Cable Length (m)	3.66	
Cable Length (in.)	144	
Shipping Dimensions (hwd / cm)	1.27 x 17.78 x 22.86	
Shipping Dimensions (hwd / in.)	0.50 x 7.00 x 9.00	
Shipping Weight (kg)	0.23	
Shipping Weight (lbs.)	0.50	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104 °F (0 to 40 °C)	
Storage Temperature Range	-4 to 140 °F (-20 to 60 °C)	
Operating Humidity Range	10 to 90%, Non-Condensing	
Storage Humidity Range	10 to 90%, Non-Condensing	
CONNECTIONS		
Side A - Connector 1	MINI DISPLAYPORT (MALE)	
Side B - Connector 1	HDMI (MALE)	
Connector Plating	Gold; Nickel	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
Displayport Specification	1.2a	
HDCP Specification	2.2	
IP68 Rated	No	
IP20 Rated	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty
Product Warranty Period (U.S. & Canada)	3-year limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies