



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

## 1.9kW Single-Phase Local Metered Automatic Transfer Switch PDU, 2 120V L5-20P / 5-20P Inputs, 16 5-15/20R Outputs, 1U, TAA

MODEL NUMBER: PDUMH20AT



### Description

Tripp Lite's Local Metered Automatic Transfer Switch / ATS PDU provides a redundant power option for single-corded network devices. Dual input cords support separate connection to PRIMARY and SECONDARY power sources. The ATS will normally maintain continuous output to all outlets as derived from the primary input cable. If the primary power source becomes unstable or fails altogether, the ATS will switch over to the secondary power source until the primary input is restored and stable. Super-fast switchover between primary and secondary power sources occurs within milliseconds. ATS functionality is supported by any two compatible AC power sources, regardless of phase angle, to support a variety of advanced redundant power networking applications. Enables fault tolerant hot-swappable UPS protection when used with a single UPS and fully redundant UPS protection when each cord is connected to a separate UPS system. In a two-UPS environment, the primary input cable must be supported by a full time sine wave UPS with zero transfer time. Tripp Lite SmartOnline series is highly recommended for use as the primary UPS in a two-UPS application. ATS configurations utilizing separate mains circuits, backup generators and even separate utility power grid feeds are fully supported. On-board ATS processor constantly evaluates power quality on both input sources to prevent transfer to the secondary source when unavailable or of lower quality than the primary source. Front input LED's display primary or secondary power availability.

### Features

- 120V 20A Automatic Transfer Switch (ATS) / Local Metered PDU (Agency de-rated to 16A continuous)
- Provides a redundant A/B power option for non-redundant networking equipment with a single input power cord
- Digital display continuously reports total output power consumption in amps
- 1U horizontal rackmount form factor; 14.5 in. / 36.8 cm depth
- 16 built-in NEMA 5-15/20R outlets (8 front / 8 rear)
- Set of two 12 ft. / 3.6m NEMA L5-20P input cables with set of two 5-20P adapters support connection to separate PRIMARY and SECONDARY inputs
- ATS circuits normally maintain output sourced from the primary input cable; As primary input power fails or becomes unstable, the ATS will switch to maintain output sourced from the secondary input cable until power on the primary input is restored and stable
- ATS configurations enable fault-tolerant, hot-swappable UPS protection when used with a single UPS and fully redundant UPS protection when each cord is connected to a separate UPS system (in a two-

### Highlights

- Single phase 16A 120V Auto Transfer Switch / ATS PDU
- Enables redundant A/B power option for single-corded network devices
- Separate primary & secondary inputs connect to any two compatible power sources
- 1U horizontal rackmount; 2 NEMA L5-20P / 5-20P inputs; 16 5-15/20R outlets
- Two digit visual current meter reports equipment load in amps; Upgrade options available
- TAA Compliant

### Package Includes

- ATS / Local Metered PDU with attached L5-20P primary input cord
- Detachable C19 to NEMA L5-20P secondary input cord
- Set of two L5-20R to 5-20P plug adapters
- 1U rackmount installation brackets
- User manual with warranty information



UPS environment, the primary input cable must be supported by an online UPS with zero transfer time similar to Tripp Lite SmartOnline series)

- Advanced ATS configurations utilizing separate mains circuits, backup generators and even separate out of phase utility power grid feeds are fully supported
- On-board ATS processor constantly evaluates power quality on both inputs to prevent transfer to the secondary source when unavailable or of lower quality than the primary source
- Super-fast switchover between primary and secondary power sources occurs in 2-7 milliseconds
- Built-in card slot supports optional SNMPWEBCARD or WEBCARDLX for permanent upgrade to a switched & monitored PDU system
- Outlets are factory programmed for sequential turn-on at 250 millisecond intervals when the PDU is first energized to prevent inrush-related equipment interaction on startup
- Front panel LEDs confirm power availability on both input lines
- Compliant with the Federal Trade Agreements Act(TAA) for GSA Schedule purchases

## Specifications

| OVERVIEW                          |  |
|-----------------------------------|--|
| UPC Code                          | 037332126665   |
| PDU Type                          | Auto-Transfer Switch; Local Metered  |
| INPUT                             |  |
| PDU Input Voltage                 | 120  |
| Recommended Electrical Service    | Two single-phase 20A 120V circuits   |
| Maximum Input Amps                | 16   |
| Maximum Input Amps Details        | Agency de-rated to 16A maximum   |
| Input Connection Type             | Primary: Attached L5-20P; Secondary: C20 inlet with detachable C19-to-L5-20P cordset; L5-20-to-L5-20P adapters       |
| PDU Plug Type                     | (2) NEMA 5-20P; (2) NEMA L5-20P  |
| Input Phase                       | Single-Phase   |
| Input Cord Details                | Set of two L5-20P cordsets with two 5-20P adapters enable connection to separate PRIMARY and SECONDARY power sources |
| Input Cord Length (ft.)           | 12   |
| Input Cord Length (m)             | 3.66   |
| OUTPUT                            |  |
| Output Capacity Details           | 1.92kW (120V) / 16A total capacity; 16A max per outlet   |
| Frequency Compatibility           | 50 / 60 Hz   |
| Output Receptacles                | (16) 5-15/20R  |
| Output Nominal Voltage            | 120V   |
| USER INTERFACE, ALERTS & CONTROLS |  |
| Front Panel LCD Display           | Digital display reports total PDU output current in amps   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                                      |  |
|--------------------------------------|--|
| Front Panel LEDs                     | 16 front panel LEDs display power on / off status for each outlet, plus 2 additional LEDs to indicate input power status for primary and secondary inputs  |
| <b>SURGE / NOISE SUPPRESSION</b>     |  |
| Automatic Shut-Off                   | No   |
| <b>PHYSICAL</b>                      |  |
| Material of Construction             | Metal  |
| Form Factors Supported               | 1U rackmount   |
| Minimum Required Rack Depth (cm)     | 49.53  |
| Minimum Required Rack Depth (inches) | 19.5   |
| PDU Form Factor                      | Horizontal (1U)  |
| Shipping Dimensions (hwd / cm)       | 13.72 x 59.18 x 51.05  |
| Shipping Dimensions (hwd / in.)      | 5.40 x 23.30 x 20.10   |
| Shipping Weight (kg)                 | 9.39   |
| Shipping Weight (lbs.)               | 20.70  |
| Unit Dimensions (hwd / in.)          | 1.75 x 17.5 x 14.5   |
| Unit Dimensions (hwd / cm)           | 4.44 x 44.4 x 36.8   |
| Unit Weight (lbs.)                   | 12.2   |
| Unit Weight (kg)                     | 5.53   |
| <b>ENVIRONMENTAL</b>                 |  |
| Operating Temperature Range          | 0C ~ 40C (32F ~ 104F)  |
| Storage Temperature Range            | -30°C to +50°C (-22°F to +122°F)   |
| Relative Humidity                    | 5-95% non-condensing   |
| Operating Elevation (ft.)            | 0-10,000   |
| Operating Elevation (m)              | 0-3000   |
| <b>COMMUNICATIONS</b>                |  |
| Network Management Cards             | SNMPWEBCARD; <a href="http://www.tripplite.com/Web-Management-Accessory-Card~WEBCARDLX">WEBCARDLX</a>  |
| SNMP Compatibility                   | Includes slot for optional SNMPWEBCARD or <a href="http://www.tripplite.com/Web-Management-Accessory-Card~WEBCARDLX">WEBCARDLX</a> ; accessory to add built-in network interface and enable remote individual outlet control over IP |
| <b>FEATURES &amp; SPECIFICATIONS</b> |  |
| TVSS Grounding                       | Rear grounding lug   |
| High Availability PDU Features       | Auto-Transfer Switching  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| STANDARDS & COMPLIANCE              |  |
|-------------------------------------|--|
| Product Certifications              | CSA (Canada); NOM (Mexico); UL 60950-1 |
| Product Compliance                  | RoHS; FCC Part 15 Class A (USA)        |
| WARRANTY                            |  |
| Product Warranty Period (Worldwide) | 2-year limited warranty                |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>