

# 1.4kW Single-Phase Local Metered PDU, 120V Outlets (16 5-15R), 5-15P, 15 ft. (4.57 m) Cord, 0U Vertical, 48 in.

MODEL NUMBER: **PDUMV15**



## Highlights

- Local Metered single phase 12A 120V 0U 48in / 122cm vertical rackmount PDU
- Two-digit current meter reports output current in amps
- Attached 15-ft. (4.57 m) cord with NEMA 5-15P input plug
- 16 NEMA 5-15R outlets
- Toolless button mount and bolt-down bracket installation hardware included

## Package Includes

- PDUMV15 Local Metered Vertical PDU
- Mounting hardware and spare mounting buttons
- Owner's manual with warranty information

## Features

- 15A single phase 120V Local Metered Power Distribution Unit / PDU (Agency de-rated to 12A continuous)
- Two-digit lighted meter reports combined total output current in amps
- Attached NEMA 5-15P 15A 120V input plug with 15-ft. (4.57 m) line cord
- 0U 48in / 122cm vertical rackmount format installs using no rack spaces
- 16 NEMA 5-15R outlets
- Includes 15A circuit breaker and lighted power switch inside a transparent protective cover
- Toolless installation supported in button-mount compatible equipment racks
- Bolt-down installation brackets support installation in other racks and additional surfaces

## Specifications

| OVERVIEW                       |                                   |
|--------------------------------|-----------------------------------|
| UPC Code                       | 037332132536                      |
| PDU Type                       | Local Metered                     |
| INPUT                          |                                   |
| PDU Input Voltage              | 120                               |
| Recommended Electrical Service | Single-phase 15A 120V service     |
| Maximum Input Amps             | 12                                |
| Maximum Input Amps Details     | Agency de-rated to 12A continuous |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                              |                                                        |
|----------------------------------------------|--------------------------------------------------------|
| PDU Plug Type                                | NEMA 5-15P                                             |
| Input Phase                                  | Single-Phase                                           |
| Input Cord Length (ft.)                      | 15                                                     |
| Input Cord Length (m)                        | 4.57                                                   |
| <b>OUTPUT</b>                                |                                                        |
| Output Capacity Details                      | 1.44kW (120V) / 12A total capacity; 12A max per outlet |
| Frequency Compatibility                      | 50 / 60 Hz                                             |
| Output Receptacles                           | (16) 5-15R                                             |
| Output Nominal Voltage                       | 120V                                                   |
| Overload Protection                          | 15A circuit breaker                                    |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                        |
| Front Panel LCD Display                      | Digital meter reports PDU output current in amps       |
| Switches                                     | Lighted on/off switch with transparent switch cover    |
| <b>SURGE / NOISE SUPPRESSION</b>             |                                                        |
| Automatic Shut-Off                           | No                                                     |
| <b>PHYSICAL</b>                              |                                                        |
| Material of Construction                     | Metal                                                  |
| Form Factors Supported                       | Vertical (0U) mounting in rack enclosures              |
| PDU Form Factor                              | Vertical (0U)                                          |
| Shipping Dimensions (hwd / cm)               | 131.50 x 8.71 x 6.10                                   |
| Shipping Dimensions (hwd / in.)              | 51.77 x 3.43 x 2.40                                    |
| Shipping Weight (kg)                         | 2.01                                                   |
| Shipping Weight (lbs.)                       | 4.43                                                   |
| Unit Dimensions (hwd / in.)                  | 48.47 x 1.5 x 1.64                                     |
| Unit Dimensions (hwd / cm)                   | 123.1 x 3.81 x 4.2                                     |
| Unit Weight (lbs.)                           | 3.74                                                   |
| Unit Weight (kg)                             | 1.70                                                   |
| <b>ENVIRONMENTAL</b>                         |                                                        |
| Operating Temperature Range                  | 0C ~ 40C (32F ~ 104F)                                  |
| Storage Temperature Range                    | -30°C to +50°C (-22°F to +122°F)                       |
| Relative Humidity                            | 5-95% Non-condensing                                   |
| Operating Elevation (ft.)                    | 0-10,000                                               |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |                                            |
|-------------------------------------|--------------------------------------------|
| Operating Elevation (m)             | 0-3000                                     |
| <b>STANDARDS &amp; COMPLIANCE</b>   |                                            |
| Product Certifications              | RETIE (Colombia); NOM (Mexico); UL 60950-1 |
| Product Compliance                  | RoHS                                       |
| <b>WARRANTY</b>                     |                                            |
| Product Warranty Period (Worldwide) | 2-year limited warranty                    |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>