

Product Use in your Country or Municipality

Tripp Lite Healthcare Product Specialist

Safe-IT Medical-Grade Power Strip, UL 1363, 6x Hospital-Grade Outlets, Antimicrobial, 1.5 ft. (0.45 m) Cord

MODEL NUMBER: PS-602-HG











Medical-grade power strip with patented antimicrobial coating and 1.5 ft. cord provides safe, versatile power distribution.

Features

Power Distribution Outside of Patient-Care Vicinities Ideal for use in administrative areas and resident rooms with no line-operated electrical equipment for diagnostic, treatment or monitoring purposes120V, 50/60 Hz power strip complies with UL 1363 specifications

Exclusive Antimicrobial ProtectionAntimicrobial coating helps resist the growth of bacteria, viruses, fungi, mold and mildewCoating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products

Versatile Medical-Grade Solution6 NEMA 5-15R-HG hospital-grade outlets provide consistent powerRugged, all-metal housing for long life in demanding environments

Premium Safety Features Resettable 15A circuit breaker protects against dangerous overloads Switchless design prevents accidental shut-off

Ready to Use Right Out of the BoxBuilt-in keyhole mounting tabs and flanges make the PS-602-HG easy to install on a variety of surfaces

Specifications

OVERVIEW	
UPC Code	037332121042

Highlights

- Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew
- Complies with UL 1363 specifications
- 1.5 ft. cord with NEMA 5-15P-HG hospital-grade plug
- Features 6 NEMA 5-15R-HG hospital-grade outlets

Package Includes

- PS-602-HG UL 1363 Medical-Grade Power Strip with six 15A Hospital-Grade Outlets and 1.5 ft. Cord
- Owner's Manual



INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A, 120V	
Input Plug Features	Hospital Grade Plug	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P-HG	
Input Cord Length (ft.)	1.5	
Input Cord Length (m)	0.46	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(6) 5-15R-HG	
Circuit Breaker (amps)	15	
Overload Protection	15 amp circuit breaker	
Transformer Accommodation	(2) Yes	
Outlet Orientation	Single row of 6	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Switches	No power switch	
PHYSICAL		
Material of Construction	Metal	
Color	White	
Power Cord Color	White	
Housing Color	White	
Included Mounting Accessories	Keyhole mounting tabs and flanges	
Mounting Holes or Slots	Yes	
Slot or Hole Mount Measurement (Center to Center)	Distance between keyhole slots = 261.92mm; Distance between end tabs = 330.17mm	
Outlets Measurement (Center to Center)	38.7mm	
Receptacle Color	White	
Shipping Dimensions (hwd / cm)	5.59 x 14.73 x 36.58	
Shipping Dimensions (hwd / in.)	2.20 x 5.80 x 14.40	





Shipping Weight (kg)	1.00	
Shipping Weight (lbs.)	2.20	
Unit Dimensions (hwd / in.)	1.5 x 13.75 x 2.5	
Unit Dimensions (hwd / cm)	3.8 x 34.9 x 6.4	
Unit Weight (lbs.)	2.00	
Unit Weight (kg)	0.91	
Mounting Details	Includes flanges	
FEATURES & SPECIFICATIONS		
Antimicrobial	Yes	
Built-in Cable Management	No	
Built-In Circuit Breaker	Yes	
Antibacterial	No	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1363; UL Listed	
Product Compliance	RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies