

2U UPS Replacement 72VDC Battery Cartridge for select Tripp Lite SmartOnline UPS

MODEL NUMBER: RBC96-2U



Highlights

- Tripp Lite-certified premium battery cartridge
- Pre-assembled and wired battery kit offers simple installation
- Rugged leak-proof construction
- Maintenance free
- Wide operating temperature range

Package Includes

- One pre-assembled 72V battery kit (consists of two strings of 12V batteries)

Description

Tripp Lite's premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery cartridge is carefully screened and certified to meet or exceed original specifications, and ships ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. See Tripp Lite's UPS replacement battery web page to confirm compatibility and quantity required.

COMPATIBLE WITH TRIPP LITE MODELS SU3000RTXL2U and SUI3000RTXL2U

Features

- Restores UPS runtime performance to original specifications
- Comes pre-assembled and ready for installation
- Reusable packaging holds expired batteries for recycling center delivery

Specifications

| OVERVIEW | |
|--------------------------------|-----------------------------------------------------|
| UPC Code | 037332146403 |
| BATTERY | |
| DC System Voltage (VDC) | 72 |
| Included Battery Set | Contains (6) 12V 9AH sealed lead acid batteries |
| Typical Battery Lifespan | 3 to 5 years, depending on UPS operating conditions |
| PHYSICAL | |
| Shipping Dimensions (hwd / cm) | 16.18 x 51.05 x 19.00 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-----------------------------------------|---------------------------|
| Shipping Dimensions (hwd / in.) | 6.37 x 20.10 x 7.48 |
| Shipping Weight (kg) | 18.60 |
| Shipping Weight (lbs.) | 41.00 |
| Unit Dimensions (hwd / in.) | 4.1 x 5.3 x 17.9 |
| Unit Dimensions (hwd / cm) | 10.4 x 13.5 x 45.5 |
| Unit Weight (lbs.) | 39.0 |
| Unit Weight (kg) | 17.69 |
| ENVIRONMENTAL | |
| Relative Humidity | 0-95% non-condensing |
| Operating Elevation (ft.) | 10,000 ft. |
| Storage Elevation (ft.) | 10,000 ft. |
| Operating Elevation (m) | 3,000 m |
| Storage Elevation (m) | 3000 m |
| WARRANTY | |
| Product Warranty Period (U.S. & Canada) | 18-month limited warranty |
| Product Warranty Period (International) | 1-year limited warranty |
| Product Warranty Period (Mexico) | 1-year limited warranty |
| Product Warranty Period (Puerto Rico) | 1-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>