

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

# 1-Outlet Personal Surge Protector, Direct Plug-In, 600 Joules, 2 Diagnostic LEDs

# MODEL NUMBER: SPIKECUBE











### Description

The SPIKECUBE Surge Suppressor from Tripp Lite is a direct plug-in suppressor providing protection on one AC outlet. Its small size makes it ideal for protecting laptop computers, projectors and other portable electronics. A green "Protected" and red "Grounded" LED illuminates to indicate that adequate surge suppression is available. The unit has 600 joules of surge energy absorption. \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

#### Features

- 1 outlet; direct plug-in
- Surge energy absorption: 600 joules; 6,500 amps
- Diagnostic LEDs indicate protection present (green) and ground present (red)
- \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

# **Specifications**

OVERVIEW		
UPC Code	037332010643	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Length Details	Direct Plug-In	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	36000	

## Highlights

- 1 outlet / direct plug-in
- 600 joule rating
- Diagnostic LEDs

#### **Package Includes**

- SPIKECUBE Surge Suppressor
- Warranty and instruction information



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

[	T	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	0	
Right-Angle Plug	No	
Input Cord Length (m)	0.00	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(1) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(1) Yes	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CON	TROLS	
Diagnostic LED(s)	Yes	
Diagnostic LED Details	Protected (green) & Grounded (red)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	600	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
UL1449 Let Through Rating	400, 500, 500	
Automatic Shut-Off	No	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Material of Construction	Plastic	
Form Factors Supported	Direct plug in suppressor supports wall-mounting directly into AC receptacle	
Housing Color	Light Gray	
Mounting Holes or Slots	No	
Receptacle Color	Gray	
Shipping Dimensions (hwd / cm)	16.51 x 10.16 x 5.08	



	1	
Shipping Dimensions (hwd / in.)	6.50 x 4.00 x 2.00	
Shipping Weight (kg)	0.10	
Shipping Weight (lbs.)	0.23	
Unit Dimensions (hwd / in.)	2.50 x 1.90 x 1.80	
Unit Dimensions (hwd / cm)	6.35 x 4.83 x 4.57	
Unit Weight (lbs.)	.100	
Unit Weight (kg)	0.05	
FEATURES & SPECIFICATIONS		
Antimicrobial	No	
Rotatable Outlets	No	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1449; UL Listed	
Product Compliance	RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$5,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies