

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

# 6-Outlet Surge Protector with 4 USB Ports (4.2A Shared) - 15 ft. (4.57 m) Cord, 5-15P Plug, 900 Joules, White

### MODEL NUMBER: TLP64USBRA15



6-outlet surge protector with USB charging safeguards your home/office electronics against dangerous surges, spikes and line noise.

#### Features

**6-Outlet Surge Protector with USB Charging Safeguards Your Sensitive Electronics**Ideal for your home or office workstation or home theater, this Protect It!® 6-outlet surge protector features a surge suppression rating of 900 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP64USBRA15 protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

**NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices**Plug your PC, printer, wireless router, game console, television, sound system or other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. Two outlets are set apart from the others to accept bulky transformers without blocking adjacent outlets.

**4 USB Ports Share 4.2 Amps of Charging Power**Four USB-A ports are available for charging your smartphone, tablet and other USB mobile devices. They share 4.2A for charging multiple devices at the same time.

**Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better** Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

**Premium Safety Features Protect Your Valuable Equipment**The lighted on/off switch provides onetouch control over connected equipment. A 15A circuit breaker protects all outlets and automatically cuts power if the protection circuit is incapacitated, preventing equipment damage. A green LED confirms your connected equipment is protected.

**Versatile Surge Protector Provides Multiple Installation Options**This surge protector with 15-ft. (4.57 m) cord and space-saving right-angle NEMA 5-15P plug allows you flexibility in placing the unit away from

#### Highlights

- 6 NEMA 5-15R outlets, including 2 designed to accommodate bulky transformers
- 900 joules protect your valuable electronics against dangerous surges and spikes
- 4 USB ports share 4.2A for fast charging of phones, tablets and other mobile devices
- 15-ft. (4.57 m) cord with rightangle NEMA 5-15P plug allows flexibility in placing devices
- Green LED reassures you at a glance that your valuable electronics are protected

#### Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge a smartphone and tablet without taking up available AC outlets

#### Package Includes

- TLP64USBRA15 6-Outlet Surge Protector, White
- Owner's manual



a wall outlet or behind furniture. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

## **Specifications**

| OVERVIEW                           |   |  |
|------------------------------------|---|--|
| UPC Code                           | 037332241238  |  |
| Device Compatibility               | Phone; Tablet; Amazon Kindle  |  |
| INPUT                              |   |  |
| Nominal Input Voltage(s) Supported | 120V AC   |  |
| Recommended Electrical Service     | 120V (110-125V)   |  |
| Input Cord Gauge Type              | 14 gauge; SJT   |  |
| Input Cord Gauge (AWG)             | 14  |  |
| Voltage Compatibility (VAC)        | 120   |  |
| Maximum Surge Amps                 | 35500   |  |
| Input Plug Type                    | NEMA 5-15P  |  |
| Input Cord Details                 | SJT   |  |
| Input Cord Length (ft.)            | 15  |  |
| Right-Angle Plug                   | No  |  |
| Input Cord Length (m)              | 4.57  |  |
| Integrated Cord Clip               | No  |  |
| OUTPUT                             |   |  |
| Frequency Compatibility            | 50 / 60 Hz  |  |
| Output (Watts)                     | 1800  |  |
| Output Receptacles                 | (6) 5-15R   |  |
| Circuit Breaker (amps)             | 15  |  |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker                         |  |
| Transformer Accommodation          | (4) Yes   |  |
| Outlet Orientation                 | Single row of 6 outlets   |  |
| Right-Angle Outlets                | No  |  |
| USER INTERFACE, ALERTS & CONTROLS  |   |  |
| Diagnostic LED(s)                  | Yes   |  |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch |  |
| Diagnostic LED Details             | Built-in LED confirms suppressor "protection present" (green) status              |  |



| CHARGING                        |  |  |
|---------------------------------|--|--|
| Number of Charging Ports        | 4  |  |
| Total Charging Watts            | 21   |  |
| Charging Method                 | USB  |  |
| Charging Port Type              | USB A (FEMALE)   |  |
| Charging Ports / Amps           | (4) 4.2A   |  |
| Overcharge Protection           | No   |  |
| SURGE / NOISE SUPPRESSION       |  |  |
| AC Suppression Joule Rating     | 900  |  |
| AC Suppression Response Time    | < 1 ns   |  |
| Protection Modes                | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |  |
| UL1449 Let Through Rating       | 800,800,800  |  |
| EMI / RFI Filtering             | Yes  |  |
| Automatic Shut-Off              | No   |  |
| DATALINE SURGE SUPPRESSION      |  |  |
| Cable (Coax) Protection         | No   |  |
| Network (Ethernet) Protection   | No   |  |
| Telephone/DSL Protection        | No   |  |
| PHYSICAL                        |  |  |
| Material of Construction        | Plastic  |  |
| Power Cord Color                | Gray   |  |
| Housing Color                   | Light Gray   |  |
| Mounting Holes or Slots         | Yes  |  |
| Receptacle Color                | Gray   |  |
| Shipping Dimensions (hwd / in.) | 11.02 x 8.70 x 1.80  |  |
| Shipping Weight (kg)            | 1.29   |  |
| Unit Dimensions (hwd / in.)     | 9.45 x 3.58 x 1.45   |  |
| Unit Dimensions (hwd / cm)      | 3.73 x 1.14 x .57  |  |
| Unit Weight (Ibs.)              | 2.10   |  |
| Unit Weight (kg)                | 0.95   |  |
| FEATURES & SPECIFICATIONS       |  |  |
| Antimicrobial                   | No   |  |
|                                 | <u> </u>   |  |



| Rotatable Outlets   | No   |  |
|---|--|--|
| GaN Technology  | No   |  |
|   |  |  |
| STANDARDS & COMPLIANCE  |  |  |
| Industry Canada (Communications)                              | Industry Canada  |  |
| Product Certifications  | CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 497A; UL 1363; UL Listed |  |
| Product Compliance  | FCC Part 68; RoHS  |  |
|   |  |  |
| WARRANTY  |  |  |
| Product Warranty Period<br>(Worldwide)                        | Lifetime limited warranty  |  |
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$25,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>            |  |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies