

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

6-Outlet Surge Protector with 4 USB Ports (4.2A Shared) - 6 ft. (1.83 m) Cord, 900 Joules, Black

MODEL NUMBER: TLP664USBB









6-outlet surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

Features

6-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics Ideal for your home or office workstation, this Protect It!® 6-outlet surge protector features a surge protection rating of 900 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP664USBB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

NEMA 5-15R Outlets Accept a Wide Range of Electronic DevicesPlug your PC, printer, wireless router, game console, television, sound system or other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. Two outlets are designed to accept bulky transformers without blocking adjacent outlets.

Surge Protector with 4 USB Ports That Share 4.2 Amps of Charging PowerFour USB-A ports are available for charging your smartphone, tablet and other USB mobile devices. .

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety FeaturesThe lighted on/off switch provides one-touch control over connected equipment. A green LED confirms your connected equipment is protected.

Versatile Surge Protector Provides Multiple Installation OptionsThis surge protector with 6-ft. (1.83 m) cord and NEMA 5-15P plug allows you flexibility in placing the unit away from a wall outlet. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

Highlights

- 6 NEMA 5-15R outlets, including 2 designed to accommodate bulky transformers
- 900 joules protect your valuable electronics against dangerous surges and spikes
- 4 USB ports share 4.2A for fast charging of phones, tablets and other mobile devices
- 6-ft. (1.83 m) cord with NEMA 5-15P plug allows flexibility in placing devices away from AC outlet
- Green LED reassures you at a glance that your valuable electronics are protected

Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

Package Includes

- TLP664USBB Protect It! 6-Outlet Surge Protector, Black
- Owner's manual



Specifications

LPC Code 037332223886 Product Type Surge Protector Charging Form Factor Strip Device Compatibility Phone; Tablet; Amazon Kindle INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Cord Gauge Type 14 gauge; SJT Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Port God Details SJT Input Cord Details SJT Input Cord Length (ft) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No Output (Watts) 1 800 Output (Watts) 1800 Output (Watts) 150 Output (Watts) 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation Single row of 6 outlets Right-Angle Outlets			
Product Type Surge Protector Charging Form Factor Strip Device Compatibility Phone; Tablet; Amazon Kindle INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Cord Gauge Type 14 gauge; SUT Input Cord Gauge (AWG) 14 Notinge Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Cord Details SUT Input Cord Length (It) 6 Right-Angle Plug No Input Cord Length (It) 8.3 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output (Watts) 1800 Output (Watts) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No <td colspan<="" th=""><th>OVERVIEW</th><th></th></td>	<th>OVERVIEW</th> <th></th>	OVERVIEW	
Charging Form Factor Strip Device Compatibility Phone: Tablet: Amazon Kindle INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Cord Gauge Type 14 gauge: SJT Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Integrated Cord Clip No Output Cord Length (m) 1.83 Integrated Cord Clip No Output (Watts) Cottput (Watts) 1800 Output (Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No <td col<="" td=""><td></td><td></td></td>	<td></td> <td></td>		
Device Compatibility Phone; Tablet, Amazon Kindle INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Cord Gauge Type 14 gauge; SJT Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Ply Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Integrated Cord Clip No Output Cord Length (m) 1.83 Integrated Cord Clip No Output Watts) 1800 Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & Combination AC circuit breaker and 2 position red illuminated on/off power switch			
INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Cord Gauge Type 14 gauge; SJT Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Charging Form Factor		
Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Cord Gauge Type 14 gauge; SJT Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off	Device Compatibility	Phone; Tablet; Amazon Kindle	
Recommended Electrical Service 120V (110-125V) Input Cord Gauge Type 14 gauge; SJT Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (ft.) 14.83 Integrated Cord Clip No VOLTPUT Frequency Compatibility No SURPUT Frequency Compatibility SO / 60 Hz Output (Watts) 150 S-15R Circuit Breaker (amps) 15 S resettable illuminated combo switch / circuit breaker Transformer Accommodation 15 Single row of 6 outlets Right-Angle Outlets No Surper Reference, ALERTS & COM-TIOLS Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	INPUT		
Input Cord Gauge Type 14 gauge; SJT Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTOLS Biagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Nominal Input Voltage(s) Supported	120V AC	
Input Cord Gauge (AWG)	Recommended Electrical Service	120V (110-125V)	
Voltage Compatibility (VAC) 120 Maximum Surge Amps 35500 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (it) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Input Cord Gauge Type	14 gauge; SJT	
Maximum Surge Amps 35500 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No Output Watts) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (d) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets Ves Switches Output Reset Switches Output Reset Illuminated on/off power switch	Input Cord Gauge (AWG)	14	
Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Output (Watts) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation 149 Single row of 6 outlets Right-Angle Outlets Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Voltage Compatibility (VAC)	120	
Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Maximum Surge Amps	35500	
Input Cord Length (ft.) Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Input Plug Type	NEMA 5-15P	
Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Input Cord Details	SJT	
Input Cord Length (m) Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Input Cord Length (ft.)	6	
Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Right-Angle Plug	No	
Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Input Cord Length (m)	1.83	
Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Integrated Cord Clip	No	
Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	OUTPUT		
Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Frequency Compatibility	50 / 60 Hz	
Circuit Breaker (amps) 15 Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Output (Watts)	1800	
Overload Protection 15A resettable illuminated combo switch / circuit breaker Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Output Receptacles	(6) 5-15R	
Transformer Accommodation (4) Yes Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Circuit Breaker (amps)	15	
Outlet Orientation Single row of 6 outlets Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Transformer Accommodation	(4) Yes	
USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Outlet Orientation	Single row of 6 outlets	
Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	Right-Angle Outlets	No	
Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	USER INTERFACE, ALERTS & CONTROLS		
	Diagnostic LED(s)	Yes	
	Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Diagnostic LED Details	Built-in LED confirms suppressor "protection present" (green) status	





CHARGING		
Number of Charging Ports	4	
Total Charging Watts	21	
Charging Method	USB	
Charging Port Type	USB A (FEMALE)	
Charging Ports / Amps	(4) 4.2A	
Overcharge Protection	No	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	900	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
UL1449 Let Through Rating	800,800,800	
EMI / RFI Filtering	Yes	
Automatic Shut-Off	No	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Material of Construction	Plastic	
Power Cord Color	Black	
Housing Color	Black	
Mounting Holes or Slots	Yes	
Receptacle Color	Black	
Shipping Dimensions (hwd / in.)	11.02 x 6.69 x 1.65	
Shipping Weight (kg)	0.75	
Unit Dimensions (hwd / in.)	9.45 x 3.58 x 1.45	
Unit Dimensions (hwd / cm)	3.72 x 1.14 x 0.57	
Unit Weight (lbs.)	1.22	
Unit Weight (kg)	0.55	
FEATURES & SPECIFICATIONS		
Antimicrobial	No	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Rotatable Outlets	No
GaN Technology	No
STANDARDS & COMPLIANCE	
Industry Canada (Communications)	Industry Canada
Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 497A; UL 1363; UL Listed
Product Compliance	FCC Part 68; RoHS
WARRANTY	
WARRANTT	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies