


Protect It! 3-Outlet Travel-Size Surge Protector, 18-in. (45.72 cm) Cord, 1050 Joules, 2-USB Charging Ports

MODEL NUMBER: TRAVELER3USB











Highlights

- 3 AC power outlets
- 1050 Joule rating
- Concealable 18-inch Power Cord
- 2 USB Charging Ports 2.1 amp total (5 VDC) for fast charging of cell phones, MP3 players, smartphones, tablets and more

Package Includes

- TRAVELER3USB Surge Suppressor
- Users Manual

Features

- 1050 joules of AC surge suppression shields equipment from the strongest surges and line noise
- 3 AC outlets with room for 1 transformer plug without blocking outlets
- 2 USB Charging Ports with 2.1 amps total is great for fast charging of cell phones, MP3 player, tablets, laptops and more.
- Portable housing with 18-in. concealable cord allow for ease of mobility and travel in briefcases
- "Protected" Diagnostic LED confirms outlet surge suppression status
- \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing
 equipment damage and indicating replacement is required

Specifications

OVERVIEW		
UPC Code	037332149626	
Product Type	Surge Protector	
Charging Form Factor	Strip	
Device Compatibility	Phone; Tablet; Amazon Kindle	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	



	T.,	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	36000	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT 3/C	
Input Cord Length (ft.)	1.5	
Right-Angle Plug	Yes	
Input Cord Length (m)	0.46	
Integrated Cord Clip	No	
OUTPUT		
Output Watt Capacity (Watts)	1800	
Frequency Compatibility	60 Hz	
Output (Watts)	1800	
Output Receptacles	(3) 5-15R	
Transformer Accommodation	(2) Yes	
Output Amp Capacity	15	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CO	NTROLS	
Diagnostic LED(s)	Yes	
Diagnostic LED Details	Built-in LED confimr suppressor "protection present" (green) status	
CHARGING		
Number of Charging Ports	2	
Total Charging Watts	10.5	
Charging Method	USB	
Charging Port Type	USB A (FEMALE)	
Charging Ports / Amps	(2) 2.1A	
Overcharge Protection	No	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1050	
Protection Modes	Includes Line to Neutral (L-N), Neutral to Ground (N-G) and Line to Ground (L-G) line surge suppression	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		





Product Compliance RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty			
Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Stots No Receptacle Color Black Shipping Dimensions (hwd / cm) 19.56 x 6.35 x 8.64 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Dimensions (hwd / in.) 0.32 Shipping Weight (kg) 0.32 Shipping Weight (kg) 0.32 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (bs.) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449, UL 1363; UL Li Product Compliance RoHS WARRANTY Product Warranty Period (Vorlanded) Lifetime limited warranty	Cable (Coax) Protection	No	
PHYSICAL Material of Construction Plastic Power Cord Color Black Mousing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / cm) 19.56 x 6.35 x 8.64 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Weight (kg) 0.32 Shipping Weight (kg) 0.70 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (bs.) 6.2 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Li Product Compliance RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Network (Ethernet) Protection	No	
Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / cm) 19.56 x 6.35 x 8.64 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Dimensions (hwd / in.) 5.70 x 2.96 x 3.40 Shipping Weight (kg) 0.32 Shipping Weight (ks) 0.70 Unit Dimensions (hwd / orn) 14.48 x 7.52 x 3.56 Unit Dimensions (hwd / orn) 14.48 x 7.52 x 3.56 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Lifetime limited warranty Product Compliance RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Telephone/DSL Protection	No	
Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / cm) 19.56 x 6.35 x 8.64 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Weight (kg) 0.32 Shipping Weight (kg) 0.70 Unit Dimensions (hwd / in.) 5.70 x 2.96 x 1.40 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Lifetime limited warranty Product Warranty Period (Worldwide) Lifetime limited warranty	PHYSICAL		
Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / cm) 19.56 x 6.35 x 8.64 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Weight (kg) 0.32 Shipping Weight (lbs.) 0.70 Unit Dimensions (hwd / in.) 5.70 x 2.96 x 1.40 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (lbs.) 62 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed (Worldwide) WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Material of Construction	Plastic	
Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / cm) 19.56 x 6.35 x 8.64 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Weight (kg) 0.32 Shipping Weight (lbs.) 0.70 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Quitets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed (Worldwide) WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Power Cord Color	Black	
Receptacle Color Black Shipping Dimensions (hwd / cm) 19.56 x 6.35 x 8.64 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Weight (kg) 0.32 Shipping Weight (lbs.) 0.70 Unit Dimensions (hwd / in.) 5.70 x 2.96 x 1.40 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (lbs.) 0.28 CONNECTIONS Number of Ports 2 Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty Lifetime limited warranty	Housing Color	Black	
Shipping Dimensions (hwd / cm) 19.56 x 6.35 x 8.64 Shipping Dimensions (hwd / in.) 7.70 x 2.50 x 3.40 Shipping Weight (kg) 0.32 Shipping Weight (lbs.) 0.70 Unit Dimensions (hwd / in.) 5.70 x 2.96 x 1.40 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (lbs.) .62 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed; UL 1449; UL 1364; UL 1449; UL	Mounting Holes or Slots	No	
Shipping Dimensions (hwd / in.)	Receptacle Color	Black	
Shipping Weight (kg) O.32 Shipping Weight (lbs.) O.70 Unit Dimensions (hwd / in.) 5.70 x 2.96 x 1.40 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (lbs.) 6.2 Unit Weight (kg) CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed Compliance WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Shipping Dimensions (hwd / cm)	19.56 x 6.35 x 8.64	
Shipping Weight (lbs.) Unit Dimensions (hwd / in.) 5.70 x 2.96 x 1.40 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (lbs.) 6.2 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed (Worldwide) WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Shipping Dimensions (hwd / in.)	7.70 x 2.50 x 3.40	
Unit Dimensions (hwd / in.) 5.70 x 2.96 x 1.40 Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (lbs.) 62 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed:	Shipping Weight (kg)	0.32	
Unit Dimensions (hwd / cm) 14.48 x 7.52 x 3.56 Unit Weight (lbs.) 62 Unit Weight (kg) 0.28 CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed (Worldwide) WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Shipping Weight (lbs.)	0.70	
Unit Weight (lbs.) Lost Weight (kg) Double Connections Number of Ports PEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No Gan Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed Compliance WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Unit Dimensions (hwd / in.)	5.70 x 2.96 x 1.40	
Unit Weight (kg) CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed: UL 1449; UL 1363; UL 1449;	Unit Dimensions (hwd / cm)	14.48 x 7.52 x 3.56	
CONNECTIONS Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed Compliance RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Unit Weight (lbs.)	.62	
Number of Ports 2 FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed Compliance RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Unit Weight (kg)	0.28	
FEATURES & SPECIFICATIONS Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed: UL 1449; UL 1363; UL 1449; UL 1363; UL 1449; UL 1449	CONNECTIONS		
Antimicrobial No Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed: Canada) Product Compliance RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Number of Ports	2	
Rotatable Outlets No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed: Canada) Product Compliance RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	FEATURES & SPECIFICATIONS		
GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL 1449; UL 1449; UL 1363; UL 1449; UL 1449	Antimicrobial	No	
STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL 1449; UL 14	Rotatable Outlets	No	
Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL UL 1449; UL 1449; UL 1449; UL 1449; UL 1449; UL 144	GaN Technology	No	
Product Compliance RoHS WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	STANDARDS & COMPLIANCE		
WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty	Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed	
Product Warranty Period (Worldwide) Lifetime limited warranty	Product Compliance	RoHS	
(Worldwide)	WARRANTY		
	Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico) \$25,000 Ultimate Lifetime Insurance-policy	Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies