

USB-A to RJ45 Serial Rollover Cable (M/M) - Cisco Compatible, 250 Kbps, 6 ft. (1.83 m), Gray

MODEL NUMBER: U209-006-RJ45-X



Connects your computer or laptop's USB port to your Cisco modem, router, firewall, switch or other serial-based Cisco device with a console port.

Features

Connects Computer's USB Port to Cisco Device Connect computer or laptop to Cisco modem, router, firewall, switch or other serial-based Cisco device with a console port
 Works with older and new Cisco models
 6 ft. long

Top-of-the-Line Performance Supports data transfer rates up to 250 Kbps
 Supports remote wake-up and power management
 Utilizes FTDI chipset.

Easy to Use No other cables or adapters needed
 No external power required
 Driver CD included (drivers also available online for download if your computer has no CD drive)

Specifications

| OVERVIEW | |
|---------------------------|--------------|
| UPC Code | 037332190017 |
| PHYSICAL | |
| Material of Construction | PVC |
| Color | Gray |
| Cable Jacket Color | Gray |
| Cable Jacket Material | PVC |
| Cable Outer Diameter (OD) | 2.5 mm |
| Wire Gauge (AWG) | 26 |

Highlights

- Supports data transfer rates up to 250 Kbps
- Supports remote wake-up and power management
- Compatible with Windows, Mac and Linux
- No cables, adapters or external power required

System Requirements

- Computer with available USB port
- Cisco device with available RJ45 console port
- Windows, Mac or Linux operating system

Package Includes

- U209-006-RJ45-X USB to RJ45 Cisco Serial Rollover Cable
- Driver CD
- Owner's manual



| | |
|--------------------------------------|-------------------------------------|
| Cable Length (ft.) | 6 |
| Cable Length (m) | 1.83 |
| Cable Length (in.) | 72 |
| Shipping Dimensions (hwd / cm) | 3.05 x 11.94 x 10.41 |
| Shipping Dimensions (hwd / in.) | 1.20 x 4.70 x 4.10 |
| Shipping Weight (kg) | 0.11 |
| Shipping Weight (lbs.) | 0.24 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 0.2425 |
| Unit Weight (kg) | 0.11 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 104°F (0 to 40°C) |
| Storage Temperature Range | -4 to 140°F (-20 to 60°C) |
| Relative Humidity | 0% to 90% RH (Non-Condensing) |
| CONNECTIONS | |
| Side A - Connector 1 | USB A (MALE) |
| Side B - Connector 1 | RJ45 (MALE) |
| Connector Plating | Gold |
| FEATURES & SPECIFICATIONS | |
| Driver Required | Yes |
| IP68 Rated | No |
| IP20 Rated | No |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>