

USB-A Port Blockers, Red, 10 Pack

MODEL NUMBER: U2BLOCK-A10-RD



Block empty USB ports to prevent accidental or unauthorized connection of devices that could upload malware or copy private data.

Features

Secure USB Port Blockers Protect Your Data Against Unauthorized Access

These port blockers are an easy way to prevent unapproved personnel from connecting an unwanted flash drive or other USB peripheral to a USB-A port. Use a Tripp Lite U2BLOCK-A-KEY security key (sold separately) to insert a blocker into the USB port and lock it into place. This will prevent any USB peripheral from infecting the device with malware or removing classified data. The key also removes the blocker just as easily and quickly as it installs the blocker. The U2BLOCK-A10-RD includes 10 red blockers, which can only be used with the key included with U2BLOCK-A-KEY.

Highlights

- Port blockers help prevent unwanted thumb drives and other devices from connecting
- Can only be locked and unlocked with Tripp Lite U2BLOCK-A-KEY (sold separately)
- Compatible with all USB-A ports in computers, hubs and wall chargers

Applications

- Protect USB device from damage or unauthorized access by blocking the port and preventing a peripheral from connecting

System Requirements

- Security key included with Tripp Lite U2BLOCK-A-KEY

Package Includes

- (10) Port blockers
- Quick Start Guide

Specifications

OVERVIEW	
UPC Code	037332253606
Accessory Type	Port Blocker
Accessory Class	USB Accessories
INPUT	
Product Length (in.)	0.28
Product Length (cm.)	0.713
Product Length (ft.)	0.02339
Product Length (m.)	0.00713
PHYSICAL	
Material of Construction	Metal, Stainless Steel, Nickel, Plastic



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Color	Red
Unit Packaging Type	Polybag
ENVIRONMENTAL	
Operating Temperature Range	-40 - 185 °F (-40 - 85 °C)
Storage Temperature Range	-58 - 221 °F (-50 - 105 °C)
Operating Humidity Range	0 - 95 % RH, Non-Condensing
Storage Humidity Range	0 - 95 % RH, Non-Condensing
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	USB A (MALE)
Connector Plating	Nickel
Contact Plating	Nickel
FEATURES & SPECIFICATIONS	
IP68 Rated	No
IP20 Rated	No
STANDARDS & COMPLIANCE	
Product Certifications	IEC/EN 62040
Product Compliance	RoHS; CE (Europe); REACH
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>