

# 4-Port USB 3.0 SuperSpeed Hub

MODEL NUMBER: U360-004-R









### Description

Tripp Lites U360-004-R USB 3.0 SuperSpeed 4-port hub carries your data from a USB3.0 enabled computer at a blazing 5Gbps transfer rate. Connect to a variety of USB enabled devices such as USB external hard drives, cameras, printers and more. Backward compatible to previous USB generations. Bus powered for use with devices that require minimal power. For more power hungry devices, an external power supply is included. Sleek, compact design is perfect for USB port expansion.

#### **Features**

- USB 3.0 SuperSpeed compatible
- 5Gbps Transfer Speed 10X as fast as USB 2.0
- Supports USB Battery Charging (BC) specification v1.2
- On bus-power, 900mA from the USB 3.0 computer port is shared between all four ports
- The included external power supply provides 2A of power, allowing each port to provide up to 1.5A of charging power to mobile devices.
- Plug-and-Play No Drivers Required
- 1 Upstream and 4 Downstream USB ports

# **Specifications**

OVERVIEW		
UPC Code	037332161154	
Product Type	Hub	
Technology	USB	
Host Connector	USB A (MALE)	
VIDEO		
Number of Monitors Supported	0	

## **Highlights**

- USB 3.0 SuperSpeed Compatible
- 5Gbps Transfer Speed 10X as fast as USB 2.0
- All 4 ports are USB Battery Charging (BC) 1.2-compliant, providing up to 1.5A for charging mobile devices
- External power supply included for use with more power hungry devices
- \*\*\*NOTE\*\*\*If your hub features white housing, see the FAQ tab on this page.

#### **System Requirements**

Windows, MAC, or Linux computer with an available USB 3.0 port

## **Package Includes**

- USB 3.0 SuperSpeed 4-Port Hub
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A)
- USB 3.0 Cable, 3-ft.
- User manual





Extended Mode	No	
Mirror Mode	No	
DATA		
Data Ports	(4) USB A (FEMALE)	
Data Ports Details	(4) USB-A - USB 3.2 Gen 1 (5 Gbps)	
INPUT		
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240	
Bus Powered	No	
POWER		
AC Adapter	Input: 100-240V, 50/60Hz, 0.35A; Output: 5V, 2A	
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.35A	
External Power Supply Output Specs (V / A)	5V / 2A	
External Power Supply Cord Length (ft.)	5	
External Power Supply Cord Length (m.)	1.5	
DC Barrel Plug	OD: 3.5 x 1.35 x 10mm, Positive Pin, Negative Sleeve	
Power Consumption (Watts)	0.7	
External Power Supply Plug(s)	NEMA 1-15P North America	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Blue (Power)	
CHARGING		
Charging Ports Details	Any of the 4 ports	
Charging Ports	(4) USB-A: 5V 1.5A (7.5W)	
PHYSICAL		
Material of Construction	ABS	
Color	Black	
Shipping Dimensions (hwd / cm)	13.59 x 7.29 x 11.99	
Shipping Dimensions (hwd / in.)	5.35 x 2.87 x 4.72	
Shipping Weight (kg)	0.28	
Shipping Weight (lbs.)	0.61	
Unit Packaging Type	Box	





0.13		
0.06		
ENVIRONMENTAL		
-4 to 158 F (-20 to 70 C)		
-4 to 185 F (-20 to 85 C)		
20% to 80% RH, Non-Condensing		
2.4 BTU/Hr		
5V 0.9A (4.5W) Output per USB Port		
4		
USB 3.0 A (MALE)		
(4) USB 3.0 A (FEMALE)		
Nickel		
FEATURES & SPECIFICATIONS		
USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)		
No		
STANDARDS & COMPLIANCE		
FCC; UL; cUL; RoHS		
RoHS; CE (Europe); REACH; FCC (USA)		
WARRANTY		
3-year limited warranty		

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>