

## USB-C to USB-B Cable (M/M) - USB 3.2, Gen 2 (10 Gbps), Thunderbolt 3 Compatible, 3 ft. (0.91 m)

MODEL NUMBER: **U422-003-G2**



Connects a computer, laptop, tablet, smartphone or other device with a USB-C port to a device or peripheral with a Type-B port, such as a hub or external hard drive.

### Features

**Supports USB 3.2 Gen 2** Recommended for smartphones, tablets, laptops, computers, external hard drives, hubs and other compatible devices Data transfer speeds up to 10 Gbps—20 times faster than USB 2.0  
**USB-B male connector** Backward compatible with previous USB generations

**USB-C Male Connector** Fumble-free reversible plug ensures fast, easy connection every time

**Premium Construction for Superior Signal Transfer** Foil and braid shielding for error-free signal quality and EMI/RFI protection Molded nickel-plated connectors and gold-plated contacts Integral strain relief for long life Rugged PVC jacket

## Specifications

OVERVIEW	
UPC Code	037332197375
Technology	USB 3.x
USB Cable Type	Passive
PHYSICAL	
Material of Construction	PVC
Color	Black
Cable Jacket Color	Black
Cable Jacket Rating	VW-1

### Highlights

- USB 3.2 Gen 2 data transfer speeds up to 10 Gbps
- Reversible USB-C male connector for fast connection the first time
- Error-free signal quality and EMI/RFI protection
- Backward compatible with previous USB generations

### System Requirements

- Device with a USB-C port
- Device with a USB Type-B port

### Package Includes

- U422-003-G2 USB 3.2 Gen 2 (10 Gbps) Cable, USB-C to USB Type-B (M/M), 3 ft.



Cable Outer Diameter (OD)	4.5MM
Cable Length (ft.)	3
Cable Length (m)	0.91
Cable Length (in.)	36
Shipping Dimensions (hwd / cm)	22.86 x 15.24 x 1.27
Shipping Dimensions (hwd / in.)	9.00 x 6.00 x 0.50
Shipping Weight (kg)	0.09
Shipping Weight (lbs.)	0.20
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	14 to 140 F (-10 to 60 C)
Storage Temperature Range	-4 to 185 F (-20 to 85 C)
Relative Humidity	10 to 85% RH, Non-Condensing
<b>CONNECTIONS</b>	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	USB B (MALE)
Connector Plating	Nickel
Contact Plating	Gold
<b>FEATURES &amp; SPECIFICATIONS</b>	
USB Specification	USB 3.2 Gen 2 (Up to 10 Gbps)
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>