

USB-C to DisplayPort 1.4 Active Adapter Cable (M/M), UHD 8K, Black/Silver, 6 ft. (1.8 m)

MODEL NUMBER: U444-006-DP8SE



USB-C to DP cable connects a DisplayPort monitor to your MacBook Pro or Windows laptop's USB-C or Thunderbolt 3 port.

Features

USB-C to DP Converter Gets Your Gaming, Home Theater or Digital Signage Setup 8K-Ready This high-speed USB Type-C to DisplayPort adapter (M/M) connects a DisplayPort monitor, projector or television to the USB-C or Thunderbolt 3 port on your MacBook Pro, Windows laptop, tablet or media center. Backward compatible with all your existing USB-C sources and DisplayPort displays, the U444-006-DP8SE is ideal for future-proofing your 1080p or 4K audio/video application in anticipation of an 8K upgrade.

Supports USB-C DisplayPort 1.4 Alternate Mode for Converting Audio/Video Signals By connecting the USB-C cable to a source device that supports USB DisplayPort 1.4 Alt Mode, you can output 8K video and digital audio to a DisplayPort monitor, television or projector without installing special software drivers. The cable is backward compatible with DP 1.2 Alt Mode signals.

Enjoy the Clarity of 4K/8K Video with Digital Audio The U444-006-DP8SE supports Ultra High Speed 8K video resolutions up to 7680 x 4320 at 30 Hz.

Reversible USB-C Connector Attaches in Either Direction Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for an instant connection every time.

Ready to Use Right from the Package, So You Can Plug and Play Immediately The plug-and-play USB Type-C to DisplayPort cable requires no software or external power. Just connect the USB-C plug to the USB-C or Thunderbolt 3 port on a source device that supports USB DisplayPort Alternate Mode, and connect the DisplayPort plug to your display.

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332255600 |

Highlights

- Ideal for future-proofing your current A/V application in anticipation of an 8K upgrade
- Converts audio/video signals from sources supporting USB DisplayPort Alt Mode
- Supports UHD resolutions up to 8K @ 30 Hz for enhanced video without latency
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Uni-directional plug-and-play cable directs signals only from USB-C to DisplayPort

Applications

- Watch 8K video from a compatible MacBook Pro, Windows laptop or media center on a compatible television, monitor or projector
- Connect a laptop to a conference table's A/V box to give a video presentation on a large screen
- Play online or PC video games that display optimal graphics
- Send 8K video content to digital signs or point-of-sale displays

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with DisplayPort input
- Both source and display devices must be compatible with 8K standards to watch 8K video

Package Includes

- U444-006-DP8SE USB-C to DisplayPort Adapter Cable, M/M, Black/Silver, 6 ft.

| | |
|--------------------------------------|--|
| Product Type | Active Cable |
| Technology | DisplayPort |
| VIDEO | |
| Max Supported Video Resolution | 8K @ 30Hz (7680 x 4320) |
| Max Supported Color Depth | 48-bit Deep Color |
| PHYSICAL | |
| Material of Construction | TPE |
| Color | Black; Gray |
| Cable Jacket Color | Black |
| Cable Jacket Material | TPE |
| Cable Outer Diameter (OD) | 4.2MM |
| Wire Gauge (AWG) | 34/24 |
| Cable Length (ft.) | 6 |
| Cable Length (m) | 1.83 |
| Cable Length (in.) | 72 |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50 |
| Shipping Weight (lbs.) | 0.15 |
| Unit Packaging Type | Polybag |
| Unit Weight (lbs.) | 0.15 |
| Unit Weight (kg) | 0.07 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 0 to 45 °C (32 to 113 °F) |
| Storage Temperature Range | -10 to 70 °C (14 to 158 °F) |
| Operating Humidity Range | 10 - 85% RH, NON-CONDENSING |
| Storage Humidity Range | 5- 90% RH, NON-CONDENSING |
| CONNECTIONS | |
| Side A - Connector 1 | USB C (MALE) |
| Side B - Connector 1 | DISPLAYPORT (MALE) |
| Contact Plating | Gold |
| FEATURES & SPECIFICATIONS | |
| Displayport Specification | 1.2; 1.4 |
| USB Specification | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps) |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

STANDARDS & COMPLIANCE

| | |
|----------------|----------------------------|
| Certifications | RoHS, REACH, CE, FCC, WEEE |
|----------------|----------------------------|

WARRANTY

| | |
|-------------------------------------|-------------------------|
| Product Warranty Period (Worldwide) | 3-year limited warranty |
|-------------------------------------|-------------------------|

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>