

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

USB-C Multiport Adapter (M/3xF) - 4K HDMI, DVI, VGA, HDCP, White

MODEL NUMBER: U444-06N-HDV4K











All-in-one converter/adapter connects a USB-C or Thunderbolt™ 3 port to an HDMI, DVI or VGA display without the need to carry separate adapters. Designed for MacBook®, Google Chromebook Pixel™ and other USB-C computers.

Description

No more carrying around separate adapters for various monitors, projectors and televisions. The U444-06N-HDV4K USB-C to HDMI/DVI/VGA All-in-One Converter Adapter connects your laptop or tablet's USB Type-C or Thunderbolt 3 port to an HDMI, DVI or VGA display. The simple all-in-one solution for displaying content on a larger screen, the U444-06N-HDV4K is ideal for use in trade shows, conference rooms, classrooms, lecture halls and anywhere else you might give a presentation.

The all-in-one unit contains separate female HDMI, DVI and HD15 ports. USB DisplayPort Alternate Mode allows audio/video signals to pass through your source device's USB-C or Thunderbolt 3 port. It supports video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz (HDMI); 1920 x 1080 (1080p) at 60 Hz (DVI); and 1920 x 1200, including 1080p (HD15) at 60 Hz. It also supports 36-bit Deep Color (12 bits per channel), 7.1-channel surround sound audio (HDMI) and HDCP 1.4.

The U444-06N-HDV4K is specifically designed for use with MacBook, Google Chromebook Pixel and all other laptops, tablets and devices equipped with a female USB-C or Thunderbolt 3 port. It's completely plug-and-play with no software, drivers or external power supply required. With its small size and built-in cable, the U444-06N-HDV4K is recommended for stowing in your laptop bag and carrying to school, the office or the latest trade show.

Features

Connects Your USB-C or Thunderbolt Laptop or Tablet to a VGA, DVI or HDMI Display

- Supports USB DisplayPort Alternate Mode for transmitting A/V signal via USB-C or Thunderbolt 3 port
- Recommended for trade shows, classrooms, lecture halls and other presentation venues

Provides Crystal-Clear, Colorful Video Images

- HDMI port supports video resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz
- DVI port supports video resolutions up to 1920 x 1080 @ 60 Hz
- HD15 port supports video resolutions up to 1920 x 1200 @ 60 Hz
- Supports 36-bit Deep Color (12 bits per channel)

Highlights

- Separate DVI, HD15 and HDMI female connectors
- HDMI port supports 4K x 2K video resolutions @ 30 Hz
- Supports USB DisplayPort Alternate Mode
- Plug and play—no software, drivers or power supply needed
- Low-profile design for easy carrying in laptop bag or briefcase

System Requirements

- Source device with USB-C or Thunderbolt 3 output that supports USB DisplayPort Alternate Mode
- Display device with HDMI, DVI or VGA input

Package Includes

- U444-06N-HDV4K USB-C to HDMI/DVI/VGA All-in-One Converter Adapter, 6 in.
- Owner's manual



Up-To-Date Technical Features

- HDMI port supports 7.1-channel surround sound audio
- Supports 300 MHz/3 Gbps per channel bandwidth (9 Gbps total)
- HDCP 1.4-compatible

Plug-and-Play Convenience

- No software, drivers or external power supply required
- Low-profile design for easy carrying in laptop bag or briefcase

Specifications

OVERVIEW	
UPC Code	037332203571
Product Type	Multiport Adapter
Technology	DVI; HDMI; VGA/SVGA
Host Connector	USB C (MALE)
VIDEO	
Video Input	USB C (MALE)
Video Output	HD15 (FEMALE); HDMI (FEMALE)
Number of Monitors Supported	1
Video Ports	HDMI (FEMALE); DVI-I DUAL LINK (FEMALE); HD15 (FEMALE)
Video Ports Details	HDMI 1.4; HDCP 1.4
Resolutions Supported	HDMI: 4K 30Hz (3840 x 2160) DVI: 1080P 60Hz (1920 x 1080) VGA: 1920 x 1200 60Hz
Supported Resolutions	1280x720 (720p); 1920x1080 (1080p); 1920x1200; 2560x1600; 3840x2160 (4K)
Max Supported Video Resolution	HDMI: 3840 X 2160 (4K X 2K) @ 30HZ, VGA: 1920 x 1200 (1080p) @ 60Hz, DVI: 1920 x 1080 (1080p) @ 60Hz
Extended Mode	No
Mirror Mode	No
Max Supported Color Depth	24-bit True Color
HDR Support	No
3D Video Supported	Yes
EDID Support	No
INPUT	
Built-In Cable Length (ft.)	0.328
Built-In Cable Length (m)	0.1
Built-In Cable Length (in.)	3.94



Built-In Cable Length (cm)	10	
Bus Powered	Yes	
Product Length (in.)	6	
Product Length (cm.)	15.24	
Product Length (ft.)	0.5	
Product Length (m.)	0.15	
BATTERY		
Battery Charging (5V/1.5A Port)	No	
POWER		
Power Consumption (Watts)	1.80	
External Power Supply	Yes	
PHYSICAL		
Material of Construction	PVC, ABS	
Color	White	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	3.9mm	
Wire Gauge (AWG)	28+34	
Shipping Dimensions (hwd / cm)	2.31 x 14.00 x 10.01	
Shipping Dimensions (hwd / in.)	0.91 x 5.51 x 3.94	
Shipping Weight (kg)	0.07	
Shipping Weight (lbs.)	0.15	
Unit Dimensions (hwd / in.)	0.6 x 3.3 x 1.8	
Unit Packaging Type	Вох	
Unit Weight (lbs.)	0.12	
Unit Weight (kg)	0.05	
ENVIRONMENTAL		
Operating Temperature Range	32 to 113 F (0 to 45 C)	
Storage Temperature Range	14 to 158 F (-10 to 70 C)	
BTUs	6.1 BTU/Hr	
Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 90% RH, Non- Condensing	
CONNECTIONS		





3		
USB C (MALE)		
DVI-I DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK)		
HD15 (FEMALE)		
HDMI (FEMALE)		
Nickel		
FEATURES & SPECIFICATIONS		
1.4		
USB 3.1 Gen 1 (up to 5 Gbps)		
No		
STANDARDS & COMPLIANCE		
CE (Europe); RoHS; REACH; FCC (USA)		
WARRANTY		
3-year limited warranty		

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies