


HEAVY-DUTY ELECTRICIAN PLIERS

ELECTRICIAN PLIERS



BULK

• Exceed ASME B107.500 standard.

	ITEM	FEATURES	TOTAL LENGTH (A)	JAW WIDTH (B)	JAW THICKNESS (C)	MAXIMUM OPENING (D)	AWG CUTTING CAPACITY	CUTS CABLE	CUTTING EDGE TYPE	CUTTING EDGE	
Side cut high leverage	268GHL 269GHL	• High leverage.	8-1/2" 9"	1-7/16" 1-7/16"	5/8" 5/8"	1-1/4" 1-1/4"	Cal. 8 Cal. 6	✓ ✓	Side Side	25/32" 25/32"	3 3
Side cut, high leverage with crimper	259GHL	• High leverage. • Wire crimper.	9-5/16"	1-29/32"	5/8"	1-9/32"	Cal. 6	✓	Side	25/32"	3
Universal with side cut and curved jaws	258G	• With narrow nose for working in narrow places.	8-17/32"	2-1/4"	9/16"	1-1/64"	Cal. 8	✓	Side	3/4"	3
Electrician with side cut	267G 268G 269G	• With knurled jaw for better grip.	7-5/16" 8-17/32" 9-5/16"	1-3/4" 2" 2-3/16"	1/2" 5/8" 5/8"	1-3/32" 1-7/32" 1-5/16"	Cal. 8 Cal. 8 Cal. 6	✓ ✓ ✓	Side Side Side	5/8" 3/4" 13/16"	3 3 6
High leverage	207GHL	• High leverage. • Angled head for working on reduced areas.	7-15/16"	13/16"	7/16"	1-1/8"	Cal. 10	✓	Diagonal	13/16"	3
High leverage diagonal cut with wire strippers	207GWS	• High leverage. • Strips solid cable 12 and 14 AWG.	7-5/16"	1-5/32"	7/16"	1-5/32"	Cal. 10	✓	Diagonal	13/16"	3
Heavy-duty diagonal cut	207G	• Conical head design brings more resistance.	7-3/4"	1-1/16"	1/2"	1/16"	Cal. 10	✓	Diagonal	1"	6
Diagonal cut, with spring	204GR 205GR 206GR	• Coiled spring for automatic opening.	4-3/16" 5-13/32" 6-1/64"	3/4" 1-3/32" 1-3/32"	1/4" 3/8" 7/16"	27/64" 21/32" 21/32"	Cal. 16 Cal. 12 Cal. 12	✓ ✓ ✓	Diagonal Diagonal Diagonal	1/2" 21/32" 25/32"	6 6 6
Diagonal cut	204G 205G 206G	• For working on reduced areas.	4-3/16" 5-13/32" 6-1/64"	1/2" 1-3/32" 1-3/32"	9/32" 7/16" 7/16"	27/64" 21/32" 21/32"	Cal. 16 Cal. 12 Cal. 12	✓ ✓ ✓	Diagonal Diagonal Diagonal	1/2" 3/4" 3/4"	6 6 6
High leverage end cut	273GHL	• High leverage. • For cutting wires or nails or simply for pulling them out.	8-3/8"	7/16"	1-3/16"	1-3/4"	Cal. 8	✓	End cutting	1-3/16"	6
High leverage long nose side cut	2292G	• Half rounded serrated jaw.	8-9/32"	2-3/8"	1/2"	1-1/16"	Cal. 8	✓	Side	5/8"	6
Long nose side cut	226G	• Half rounded serrated jaw.	6-5/8"	2-1/4"	3/8"	3/4"	Cal. 10	✓	Side	1/2"	6
Long nose side cut with spring	226GR	• Half rounded serrated jaw. • Coiled spring for automatic opening.	6-5/8"	2-1/4"	3/8"	3/4"	Cal. 10	✓	Side	1/2"	6
Round nose side cutting	226GS	• Half rounded serrated jaw.	6-1/4"	1-29/32"	3/8"	3/4"	Cal. 10	✓	Side	1/2"	6
Long nose, non cutting	282G	• Half rounded serrated jaw.	4-3/4"	1-5/16"	1/4"	27/64"	n/a	✗	-	-	6
Long nose, non cutting with spring	282GR	• Half rounded serrated jaw. • Coiled spring for automatic opening.	4-3/4"	1-5/16"	1/4"	27/64"	n/a	✗	-	-	6
Flat long nose, non cutting	227G	• Flat nose serrated jaw. • Long nose for working on reduced areas.	6-5/8"	2-1/4"	3/8"	3/4"	n/a	✗	-	-	6
Flat, conical long nose, non cutting	220G	• Conical design for working on reduced areas. • Knurled jaws for better grip in precision operations.	6-5/8"	2-1/4"	3/8"	3/4"	n/a	✗	-	-	6
45° offset extra long nose, non cutting	241G	• Half rounded serrated jaw. • Long desing and 45° angled head for hard to reach and obstructed operations.	9-5/8"	2-11/16"	3/8"	11/16"	n/a	✗	-	-	1
Extra long straight nose, non cutting	239G	• Half rounded serrated jaw. • Long desing for hard to reach operations.	11"	3"	7/16"	5/8"	n/a	✗	-	-	1

PLIERS, SNIPS AND CUTTERS