VALUTEK DATA SHEET | APPAREL

Valutek 3-Ply Polypropylene Face Mask





Valutek's disposable 3-ply polypropylene face mask is constructed from non-woven pleated, 7" x 3½" rectangular, glass-free polypropylene material with a malleable flat aluminum noseband. It's available in both floss-covered round elastic ear-loops and headband designs.

All Valutek masks are tested and manufactured in ISOcompliant facilities under Valutek inspection and stringent process control to ensure compliance with Valutek quality standards and product specifications.

Part Number: VTMASK

Features

- 3-ply material provides excellent guard against bacteria and particulates
- Malleable aluminum noseband ensures adjustable
 proper seal and perfect fitting
- Disposable, lightweight with very low breathing resistance
- High filtration capacity
- Without glass fibers
- Available in both elastic ear loops and head band design.

Application

As part of the Valutek Microtek product family, this product is recommended for use in cleanrooms Class 100-1,000 (ISO 5-6) critical environments.

Color Option

Version 3.0 | 10.25.2023

White and Blue

Packaging



- 50 ea/bag, 20 bags/case, 1000 ea/case.
- Flat packed with a carton liner.
- Critical environment compatible.
- Part number and lot number traceable.



www.valutek.com

Valutek 3-Ply Polypropylene Face Mask

Part Number: VTMASK



VTMASK Physical Properties

Part Number	Style	Color
VTMASKELR-WH	Elastic Ear Loops	White
VTMASKELR-BL	Elastic Ear Loops	Blue
VTMASKHB-WH	Head Band	White

VTMASK Technical Performance

Propery	Result	Test Method
Filtration Efficiency (>0.5um)	> 86.5% avg	ASTM F2101
Air Permeability		
Breath Thwart	< 23.5 Pa	
Breath Thwart Upswing	< 98.0 Pa	
Wet Thwart	< 51.5 Pa	IEST-RP-CC-003
Cease Chamber	< 180 ml	
Cu.ft/minute/sq.ft	35.41 average	

*Note: Technical data listed reflects upper/lower limits. Certificates of Analysis available upon request for actual lot-tolot test data.



valutek.com