

Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

## 1. Product and company identification

1.1 Identification of the substance or preparation:

Trade name WACKER SilGel® 612 B

Product group: Silicone Gel

Use of the Substance/Mixture Industrial.

Potting compound

1.2 Company/undertaking identification:

Manufacturer/distributor: Wacker Chemical Corporation

4950 S State Road Ann Arbor, MI 48108

USA

Customer information: InfoLine:

Tel (517) 264-8240 Hours of operation:

Monday - Friday, 8 am to 5 pm (eastern standard time)

Corporate website: www.wacker.com

Emergency telephone no. (24h): (517) 264-8500

Transportation emergency: (800) 424-9300 (CHEMTREC, USA)

(703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

# 2. Hazards identification

## 2.1 Classification of the substance or mixture

## Classification (GHS):

Not a hazardous substance or mixture.

#### 2.2 Label elements

#### Labelling (GHS):

No labeling according to GHS required.

#### 2.3 Other hazards

No data available.

Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 3. Composition/information on ingredients

#### 3.1 Chemical characterization (preparation)

Chemical characterization

Polydimethylsiloxane with functional groups and auxiliaries for addition cross-linking

#### 3.2 Information on ingredients:

This material does not contain any ingredients above the permitted limit(s).



Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

# 4. First-aid measures

#### 4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

#### 4.2 If inhaled

Material cannot be inhaled under normal conditions. No special treatment required.

#### 4.3 In case of skin contact

After skin contact wipe off excess material with cloth or paper. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

#### 4.4 In case of eye contact

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

#### 4.5 If swallowed

No special measures are required after swallowing.

# 5. Fire-fighting measures

### 5.1 Flammable properties:

Property:	Value:	Method:
Flash point	> 200 °C (> 392 °F)	(DIN 51376)
Boiling point/boiling range	not applicable	
Lower explosion limit	exempt	
Upper explosion limit	exempt	
Ignition temperature	> 450 °C (> 842 °F)	(DIN 51794)
NFPA Hazard Class (comb./flam.liquid)	IIIB	

#### 5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

# 5.3 Recommended extinguishing media:

water-mist, carbon dioxide, sand, dry chemical or alcohol-resistant foam.

## 5.4 Unsuitable extinguishing media:

water-spray, sharp water jet.

#### 5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide and incompletely burnt hydrocarbons .

# 5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.

# 6. Accidental release measures

#### 6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.



Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

#### HAZWOPER PPE Level: D

#### 6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

#### 6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

# 7. Handling and storage

### 7.1 Handling

#### Precautions for safe handling:

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

#### Precautions against fire and explosion:

Observe the general rules for fire prevention.

# 7.2 Storage

# Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

#### Advice for storage of incompatible materials:

Observe local/state/federal regulations.

#### Further information for storage:

Store in a dry and cool place.

# 8. Exposure controls and personal protection

#### 8.1 Engineering controls

#### Ventilation:

Use with adequate ventilation.

#### Local exhaust:

not necessary

# 8.2 Associate substances with specific control parameters such as limit values

## Maximum airborne concentrations at the workplace:

Substance	Type	ma/m³	mag	Dust fract.	
Oubstation	I ypc	mig/m	ppiii	Dust Hact.	

none known

# 8.3 Personal protection equipment (PPE)

#### Respiratory protection:

Respiratory protection is not normally required.

## Hand protection:

Recommendation: Any liquid-tight rubber or vinyl gloves.

#### Eye protection:

Recommendation: Safety glasses with side shields.



Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

#### Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

#### 8.4 General hygiene and protection measures:

When handling do not eat, drink, smoke or apply cosmetics. Wash thoroughly after handling.

# 9. Physical and chemical properties

# 9.1 Appearance

Physical state : liquid
Colour : colourless
Odour : odourless

## 9.2 Safety data

 Property:
 Value:
 Method:

 Melting point.
 not applicable

 Boiling point/boiling range.
 not applicable

 Flash point.
 > 200 °C (> 392 °F)
 (DIN 51376)

 Ignition temperature.
 > 450 °C (> 842 °F)
 (DIN 51794)

Lower explosion limit......: exempt
Upper explosion limit......: exempt
Vapour pressure....: exempt

Water solubility practically insoluble at 20 °C (68 °F) pH Not applicable. Insoluble in water.

Partition coefficient: n-octanol/water not applicable

Viscosity, kinematic...... no data available

#### 9.3 Further information

No data available.

## 10. Stability and reactivity

#### 10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

#### 10.2 Conditions to avoid

None known.

#### 10.3 Materials to avoid

None known.

#### 10.4 Hazardous decomposition products

If stored and handled properly: none known. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

### 10.5 Further information:

Hazardous polymerization cannot occur.

# 11. Toxicological information

#### 11.1 Information on toxicological effects

#### 11.1.1 Acute toxicity



Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

#### Product details:

Exposure routes	Result/Effect
Oral LD50 > 2000 mg/kg	
	Neither mortality nor clinical signs of toxicity were observed with the given dose.
	Species: Rat, Method: OECD 423, Source: Conclusion by analogy
dermal	LD50 > 2000 mg/kg
	Species: Rabbit, Source: Expert judgement

#### 11.1.2 Skin corrosion/irritation

#### **Product details:**

No skin irritation

(Species: Rabbit, Source: Conclusion by analogy)

#### 11.1.3 Serious eye damage/eye irritation

#### **Product details:**

No eye irritation (Species: Rabbit, Source: Conclusion by analogy)

#### 11.1.4 Respiratory or skin sensitisation

#### Product details:

Exposure routes	Result	
Skin contact	Does not cause skin sensitisation.	
	(Species: Guinea pig, Test system: Buehler Test, Method: OECD 406, Source: Conclusion by analogy)	
Inhalation	No data available.	

#### 11.1.5 Germ cell mutagenicity

#### **Assessment:**

For this endpoint no toxicological test data is available for the whole product.

#### 11.1.6 Carcinogenicity

#### **Assessment:**

For this endpoint no toxicological test data is available for the whole product.

## 11.1.7 Reproductive toxicity

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

### 11.1.8 Specific target organ toxicity - single exposure

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

#### 11.1.9 Specific target organ toxicity - repeated exposure

#### Accessment.

For this endpoint no toxicological test data is available for the whole product.

#### 11.1.10 Aspiration hazard

# Assessment:

For this endpoint no toxicological test data is available for the whole product.

#### 11.1.11 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

#### 11.1.12 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other information: None known.

# 12. Ecological information

#### 12.1 Toxicity

#### **Assessment:**

Based on available data no effects on aquatic organisms that are relevant for classification must be expected for the product up to its limits of water solubility. According to current knowledge adverse effects on water purification plants are not expected.

#### Product details:

Result/Effect	Species/Test system	Source
LL50: > 1000 mg/l (nominal)	static test	literature
The effect level is greater than the maximum achievable	Fish (96 h)	(Polydimethylsiloxan
concentration. The value refers to the water-		e)
accommodated fraction (WAF).		
EC50: > 0.0001 mg/l (measured)	static test	literature
The effect level is greater than the maximum achievable	Daphnia magna (Water flea) (48 h)	(Polydimethylsiloxan
concentration. The value refers to the water-		e)
accommodated fraction (WAF).		
IC50 (Growth rate): > 100000 mg/l (nominal)	static test	literature
The effect level is greater than the maximum achievable	Skeletonema costatum (marine diatom) (72 h)	(Polydimethylsiloxan
concentration. The value refers to the water-		e)
accommodated fraction (WAF).		
NOEC: > 10000 mg/kg	feeding study	literature
	Oncorhynchus mykiss (rainbow trout) (28 d)	(Polydimethylsiloxan e)
NOEC (mortality): > 500 mg/kg	exposure via sediment	literature
The exposure to treated sediment did not result in	Daphnia magna (Water flea) (21 d)	(Polydimethylsiloxan
effects.		e)
NOEC (Growth): > 500 mg/kg	exposure via sediment	literature
The exposure to treated sediment did not result in	Daphnia magna (Water flea) (21 d)	(Polydimethylsiloxan
effects.		e)
NOEC (reproduction rate): > 500 mg/kg	exposure via sediment	literature
The exposure to treated sediment did not result in effects.	Daphnia magna (Water flea) (21 d)	(Polydimethylsiloxan e)

### 12.2 Persistence and degradability

## **Assessment:**

Silicone content: biologically not degradable. Elimination by adsorption to activated sludge.

# 12.3 Bioaccumulative potential

## Assessment:

Polymer component: Bioaccumulation is not expected to occur.

# 12.4 Mobility in soil

## Assessment:

Polymer component: insoluble in water. Adsorbs on soil.

#### 12.5 Results of PBT and vPvB assessment

No data available.



Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

#### 12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

none known

# 13. Disposal considerations

#### 13.1 Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

#### 13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

# 14. Transport information

#### 14.1 US DOT & CANADA TDG SURFACE

Valuation .....: Not regulated for transport

14.2 Transport by sea IMDG-Code

Valuation .....: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation .....: Not regulated for transport

# 15. Regulatory information

#### 15.1 U.S. Federal regulations

#### TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

#### TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

#### **CERCLA Regulated Chemicals:**

This material does not contain any CERCLA regulated chemicals.

#### SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

### SARA 311/312 Hazard Class:

No SARA Hazards

#### **SARA 313 Chemicals:**

This material does not contain any SARA 313 chemicals above de minimus levels.

## **HAPS (Hazardous Air Pollutants):**

CAS-No.	Chemical	Upper limit wt. %
108-88-3	Toluene	<=0.0060

### 15.2 U.S. State regulations

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):



Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

This material does not contain any chemicals known to the State of California to cause cancer.

California Proposition 65 Reproductive Toxins:

108-88-3 Toluene

#### **Massachusetts Substance List:**

This material contains no listed components.

#### Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

#### 15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan:	ENCS (Handbook of Existing and New Chemical Substances):
·	This product is listed in, or complies with, the substance inventory.
New Zealand:	NZIoC (New Zealand Inventory of Chemicals):
	This product is listed in, or complies with, the substance inventory. (For a correct
	interpretation of the New Zealand status, additional information like GHS
	classification or Group Standard is required.)
Australia:	AIIC (Australian Inventory of Industrial Chemicals):
	This product is listed in, or complies with, the substance inventory.
China:	IECSC (Inventory of Existing Chemical Substances in China):

Canada....: DSL (Domestic Substance List):

United States of America (USA) ...... TSCA (Toxic Substance Control Act Chemical Substance Inventory):

All components of this product are listed as active or are in compliance with the

substance inventory.

This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of

this obligation.

European Economic Area (EEA) ...... REACH (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other dewestroom upons must be fulfilled by the latter.

Please approach your regular contact for more detailed information.

#### 16. Other information

#### 16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details



Material: 60004783 WACKER SilGel® 612 B

Version 2.4 (US) Print Date 12/21/2022 Date of last alteration: 11/09/2022

please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

#### 16.2 **Glossary of Terms:**

ACGIH - American Conference of Governmental Industrial

Hygienists

**DOT** - Department of Transportation

hPa - Hectopascals

mPa\*s - Milli Pascal-Seconds

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

ppm - Parts per Million

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit TSCA - Toxic Substances Control Act TWA - Time Weighted Average

Flash point determination methods ...... Common name

ASTM D92, DIN 51376, ISO 2592 ...... Cleveland open cup

ASTM D3278, DIN 55680, ISO 3679 ...... Setaflash or Rapid closed cup

ASTM D93, DIN 51758, ISO 2719 ...... Pensky-Martens closed cup

#### 16.3 Conversion table:

Pressure:..... 1 hPa \* 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa

Viscosity: ...... 1 mPa\*s = 1 centipoise (cP)