



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

1. Product and company identification

1.1 Identification of the substance or preparation:

Commercial product name:	ELASTOSIL® M 4601 B
Use of substance / preparation	Industrial. Raw material for: elastomer products .

1.2 Company/undertaking identification:

Manufacturer/distributor:	DRAWIN Vertriebs-GmbH Rudolf-Diesel-Straße 15 85521 Riemerling Germany
Customer information:	Wacker Chemical Corporation 3301 Sutton Road Adrian, Michigan 49221-9397 USA InfoLine: Tel (517) 264-8240 Hours of operation: Monday - Friday, 8 am to 5 pm (eastern standard time) Corporate website: www.wacker.com
Emergency telephone no. (24h):	(517) 264-8500
Transportation emergency:	(800) 424-9300 (CHEMTREC, USA) (703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (GHS):
Not a hazardous substance or mixture.

2.2 Label elements

Labelling (GHS):
No labeling according to GHS required.

2.3 Other hazards

No data available.

3. Composition/information on ingredients

3.1 Chemical characterization (preparation)

Chemical characteristics
Polydimethylsiloxane with functional groups and auxiliaries for addition cross-linking

3.2 Information on ingredients:

This material does not contain any ingredients above the permitted limit(s).



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above $\geq 0.1\%$.

4. First-aid measures

4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

4.2 After inhalation

Material cannot be inhaled under normal conditions. No special treatment required.

4.3 After contact with the skin

After skin contact wipe off excess material with cloth or paper. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

4.5 After swallowing

No special measures are required after swallowing.

5. Fire-fighting measures

5.1 Flammable properties:

Property:	Value:	Method:
Flash point.....	> 300 °C (> 572 °F)	(ISO 2592)
Boiling point / boiling range	not applicable	
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL).....	not applicable	
Ignition temperature	> 450 °C (> 842 °F)	(DIN 51794)
NFPA Hazard Class (comb./flam.liquid)	IIIB	

5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

5.3 Recommended extinguishing media:

water-mist , carbon dioxide , sand , dry chemical or alcohol-resistant foam .

5.4 Unsuitable extinguishing media:

water-spray , sharp water jet .

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

not applicable

5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

6. Accidental release measures

6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: D

6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

7. Handling and storage

7.1 General information:

Always stir well before use.

7.2 Handling

Precautions for safe handling:

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

Precautions against fire and explosion:

Observe the general rules for fire prevention.

7.3 Storage

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place.

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use with adequate ventilation.

Local exhaust:

not necessary

8.2 Associate substances with specific control parameters such as limit values

none known



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

8.3 Personal protection equipment (PPE)

Respiratory protection:

Respiratory protection is not normally required.

Hand protection:

Recommendation: Any liquid-tight rubber or vinyl gloves.

Eye protection:

Recommendation: Safety glasses with side shields.

Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

When handling do not eat, drink, smoke or apply cosmetics. Wash thoroughly after handling.

9. Physical and chemical properties

9.1 Appearance

Physical state : liquid
Colour : red brown
Odour : odourless

9.2 Safety parameters

Property:	Value:	Method:
Melting point / melting range	not determined	
Boiling point / boiling range	not applicable	
Flash point.....	> 300 °C (> 572 °F)	(ISO 2592)
Ignition temperature	> 450 °C (> 842 °F)	(DIN 51794)
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL).....	not applicable	
Vapour pressure.....	not determined	
Density	1.01 g/cm ³ at 20 °C (68 °F), at 1013 hPa	(DIN 51757)
Water solubility / miscibility.....	virtually insoluble at 20 °C (68 °F)	
pH-Value	not applicable	
Viscosity (dynamic)	ca. 800 mPa.s at 20 °C (68 °F)	(Brookfield)

9.3 Further information

Odour limit..... : no data available
Thermal decomposition..... : > 200 °C (> 392 °F)

10. Stability and reactivity

10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

none known

10.3 Materials to avoid

none known

10.4 Hazardous decomposition products

If stored and handled properly: none known . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

11. Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
Oral	LD50: > 2000 mg/kg	Rat	Conclusion by analogy
dermal	LD50: > 2000 mg/kg	Rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by analogy

11.1.3 Serious eye damage / eye irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by analogy

11.1.4 Respiratory or skin sensitization

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
dermal	not sensitizing	Guinea pig; Buehler Test	Conclusion by analogy OECD 406

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

11.1.10 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.11 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

12. Ecological information

12.1 Toxicity

Assessment:

Based on available data no effects on aquatic organisms that are relevant for classification must be expected for the product up to its limits of water solubility. According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Separation by sedimentation.

12.3 Bioaccumulative potential

Assessment:

Polymer component: Bioaccumulation is not expected to occur.

12.4 Mobility in soil

Assessment:

Silicone content: Insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

none known

13. Disposal considerations

13.1 Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation: Not regulated for transport



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

14.2 Transport by sea IMDG-Code

Valuation: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation: Not regulated for transport

15. Regulatory information

15.1 U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

This product does not present any SARA 311/312 hazards.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

15.2 U.S. State regulations

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This material does not contain any chemicals known to the State of California to cause cancer.

This material does not contain any chemicals known to the State of California to cause reproductive effects.

Massachusetts Substance List:

1309-37-1 Iron oxide

New Jersey Right-to-Know Hazardous Substance List:

1309-37-1 Iron oxide

Pennsylvania Right-to-Know Hazardous Substance List:

1309-37-1 Iron oxide

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan: **ENCS** (Handbook of Existing and New Chemical Substances):

This product is listed in, or complies with, the substance inventory.

New Zealand: **NZIoC** (New Zealand Inventory of Chemicals):

This product is listed in, or complies with, the substance inventory. (For a correct interpretation of the New Zealand status, additional information like GHS classification or Group Standard is required.)

Australia: **AICS** (Australian Inventory of Chemical Substances):

This product is listed in, or complies with, the substance inventory.

China.....: **IECSC** (Inventory of Existing Chemical Substances in China):

This product is listed in, or complies with, the substance inventory.

Canada: **DSL** (Domestic Substance List):

This product is listed in, or complies with, the substance inventory.



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

Philippines.....	: PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	: TSCA (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan	: TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA).....	: REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea)	: AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"): General note: in case of registration obligations for substances or polymers imported into Korea or manufactured within Korea these are fulfilled by the supplier mentioned in section 1. The registration obligations for substances or polymers imported into Korea by customers or other downstream users must be fulfilled by the latter.

16. Other information

16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists
DOT - Department of Transportation
hPa - Hectopascals
mPa*s - Milli Pascal-Seconds
OSHA - Occupational Safety and Health Administration
PEL - Permissible Exposure Limit

ppm - Parts per Million
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
WHMIS - Canadian Workplace Hazardous Materials Identification System

Flash point determination methods	Common name
ASTM D56.....	Tagliabue (Tag) closed cup
ASTM D92, DIN 51376, ISO 2592	Cleveland open cup
ASTM D93, DIN 51758, ISO 2719	Pensky-Martens closed cup
ASTM D3278, DIN 55680, ISO 3679	Setaflash or Rapid closed cup
DIN 51755.....	Abel-Pensky closed cup



DRAWIN

Safety Data Sheet

Material: 60007348

ELASTOSIL® M 4601 B

Version: 2.3 (US)

Date of print: 05/25/2022

Date of last alteration: 11/16/2019

16.3 Conversion table:

Pressure:.....: 1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa

Viscosity:.....: 1 mPa*s = 1 centipoise (cP)