

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

1. Product and company identification

1.1 Identification of the substance or preparation:

Trade name ELASTOSIL® E43 N TRANSPARENT
Product group: RTV Adhesive Sealant
Use of the Substance/Mixture Industrial.
Adhesive / sealant .

1.2 Company/undertaking identification:

Manufacturer/distributor: Wacker Chemical Corporation
4950 S State Road
Ann Arbor, MI 48108
USA
Customer information: InfoLine:
Tel (517) 264-8240
Hours of operation:
Monday - Friday, 8 am to 5 pm (eastern standard time)
Corporate website: www.wacker.com
Emergency telephone no. (24h): (517) 264-8500
Transportation emergency: (800) 424-9300 (CHEMTREC, USA)
(703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (GHS):

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (GHS):

No labeling according to GHS required.

2.3 Other hazards

No data available.

Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

3. Composition/information on ingredients

3.1 Chemical characterization (preparation)

Chemical characterization

Polydimethylsiloxane and fillers and auxiliaries and acetoxysilane cross-linker

3.2 Information on ingredients:

Type	CAS-No.	Substance	Content [wt. %]		Note
			Lower	Upper	
INHA	4253-34-3	Triacetoxymethylsilane		<5.0	

Type: HYD - by-product upon hydrolysis, INHA - ingredient, NEBE - by-product, MONO - residual monomer, VERU - impurity, VUL - by-product upon vulcanization. *** **Note:** C1 - IARC carcinogen, C2 - NTP carcinogen, C3 - OSHA carcinogen, NH - non-hazardous, R - reproductive toxin.

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above $\geq 0.1\%$.

4. First-aid measures

4.1 General information:

Get medical attention if irritation occurs or if breathing becomes difficult.

4.2 If inhaled

If inhaled, remove to fresh air.

4.3 In case of skin contact

Remove material with a waterless skin cleaner from skin and clothing immediately. Wash then with plenty of water or water and soap.

4.4 In case of eye contact

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min. Get medical attention.

4.5 If swallowed

If swallowed, do not induce vomiting. Induce drinking plenty of water in small portions. Get medical attention immediately. Show label.

5. Fire-fighting measures

5.1 Flammable properties:

Property:	Value:	Method:
Flash point.....	not applicable	
Boiling point/boiling range	not applicable	
Lower explosion limit.....	not applicable	
Upper explosion limit.....	no data available	
Ignition temperature	453 °C (847 °F)	(EN 14522)
NFPA Hazard Class (comb./flam.liquid).....	Not applicable	

5.2 Fire and explosion hazards:

Consider possible formation of explosive mixtures with air, for example in uncleaned containers.

5.3 Recommended extinguishing media:

water-spray , carbon dioxide , dry chemical or alcohol-resistant foam .

5.4 Unsuitable extinguishing media:

sharp water jet

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide , nitrogen oxides and incompletely burnt hydrocarbons .

5.6 Fire fighting procedures:

Cool endangered containers with water. Fire fighters should wear full protective clothing including a self-contained breathing apparatus.

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

6. Accidental release measures

6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: D

6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

6.4 Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

7. Handling and storage

7.1 Handling

Precautions for safe handling:

Ensure adequate ventilation. Must be syphoned off in situ. Keep away from incompatible substances in accordance with section 10. Observe information in section 8.

Precautions against fire and explosion:

Product may release acetic acid. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Storage

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

Minimum temperature allowed during storage and transportation: 0 °C (32 °F)

Maximum temperature allowed during storage and transportation: 35 °C (95 °F)

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use only with adequate ventilation.

Local exhaust:

In case of potential decomposition products: Local exhaust ventilation which meets the requirements of ANSI Z9.2 is recommended to control airborne contaminants at the point of use.

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

8.2 Associate substances with specific control parameters such as limit values

Maximum airborne concentrations at the workplace:

Substance	Type	mg/m ³	ppm	Dust fract.
Acetic acid	OSHA PEL	25.0	10.0	
Acetic acid	ACGIH TWA		10.0	

Re Acetic acid (CAS-no. 64-19-7): STEL is 15 ppm (ACGIH).

8.3 Personal protection equipment (PPE)

Respiratory protection:

Respiratory protection is not normally required.

Hand protection:

Any liquid-tight rubber or vinyl gloves.

Eye protection:

Safety glasses with side shields or chemical safety goggles.

Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required.

8.4 General hygiene and protection measures:

Avoid contact with eyes, skin and clothing. Avoid breathing dust/vapor/mist/gas/aerosol. When handling do not eat, drink, smoke or apply cosmetics. Wash thoroughly after handling.

9. Physical and chemical properties

9.1 Appearance

Physical state: liquid (23 °C (73 °F) / 1,013 hPa)
Form: paste
Colour: colourless
Odour: pungent

9.2 Safety data

Property:	Value:	Method:
Melting point.....	not applicable	
Boiling point/boiling range	not applicable	
Flash point.....	not applicable	
Ignition temperature	453 °C (847 °F)	(EN 14522)
Lower explosion limit.....	not applicable	
Upper explosion limit.....	no data available	
Vapour pressure.....	not applicable	
Density	1.11 g/cm ³ at 23 °C (73 °F), at 1013 hPa	(DIN EN ISO 2811-2)
Water solubility.....	insoluble at 20 °C (68 °F)	
pH	Not applicable. Product displays acidic reaction with water.	
Partition coefficient: n-octanol/water	not applicable	
Viscosity, dynamic.....	250000 mPa.s at 25 °C (77 °F) shear rate: 0.5 1/S	(DIN EN ISO 3219)
Viscosity, dynamic.....	150000 mPa.s at 25 °C (77 °F) shear rate: 25 1/S	(DIN EN ISO 3219)
Viscosity, kinematic.....	no data available	

9.3 Further information

Explosion limits for released acetic acid: 4 - 17%(V).

Odour Threshold: no data available
Thermal decomposition.....: no data available

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

10. Stability and reactivity

10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

Moisture, heat, open flames, and other sources of ignition.

10.3 Materials to avoid

Reacts with: water, basic substances and alcohols. The reaction takes place with the formation of acetic acid.

10.4 Hazardous decomposition products

Acetic acid by hydrolysis. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

11. Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product details:

Exposure routes	Result/Effect
Oral	LD50 > 2000 mg/kg Species: Rat, Source: Expert judgement
dermal	LD50 > 2000 mg/kg Species: Rabbit, Source: Expert judgement

11.1.2 Skin corrosion/irritation

Product details:

No skin irritation
Bridging principle "Substantially similar mixtures".
(Species: Rabbit, Method: OECD 404)

11.1.3 Serious eye damage/eye irritation

Product details:

No eye irritation
Bridging principle "Substantially similar mixtures".
(Species: Bovine cornea, Test system: in vitro assay, Method: OECD 437)
No eye irritation
Bridging principle "Substantially similar mixtures".
(Species: Rabbit, Method: OECD 405)

11.1.4 Respiratory or skin sensitisation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Product details:

Exposure routes	Result
Inhalation	No data available.

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity - single exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity - repeated exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

11.1.11 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

11.1.12 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other information: In contact with dampness product separates a small quantity of acetic acid (64-19-7) which irritates skin and mucous membranes.

12. Ecological information

12.1 Toxicity

Assessment:

Evaluation on basis of physical-chemical properties: No expected damaging effects to aquatic organisms.

12.2 Persistence and degradability

Assessment:

Polymer component: biologically not degradable. Elimination by adsorption to activated sludge.

12.3 Bioaccumulative potential

Assessment:

Polymer component: No adverse effects expected.

12.4 Mobility in soil

Assessment:

Polymer component: insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

none known

13. Disposal considerations

13.1 Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation: Not regulated for transport

Other Information: Protect from freezing, when exposed to cold temperatures approaching 0 °C (32 °F) or below.

14.2 Transport by sea IMDG-Code

Valuation: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation: Not regulated for transport

15. Regulatory information

15.1 U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

No SARA Hazards

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

HAPS (Hazardous Air Pollutants):

CAS-No.	Chemical	Upper limit wt. %
108-88-3	Toluene	<=0.0238

15.2 U.S. State regulations

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This material does not contain any chemicals known to the State of California to cause cancer.

California Proposition 65 Reproductive Toxins:

108-88-3 Toluene

Massachusetts Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan	ENCS (Handbook of Existing and New Chemical Substances): This product is listed in, or complies with, the substance inventory.
Australia	AIIC (Australian Inventory of Industrial Chemicals): This product is listed in, or complies with, the substance inventory.
China.....	IECSC (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.
Canada	DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines.....	PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	TSCA (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan	TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA).....	REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea)	AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"): Please approach your regular contact for more detailed information.

16. Other information**16.1 Additional information:**

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

Safety Data Sheet

Material: 60073019

ELASTOSIL® E43 N TRANSPARENT

Version 3.7 (US)

Print Date 05/02/2023

Date of last alteration: 11/09/2022

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists

DOT - Department of Transportation

hPa - Hectopascals

mPa*s - Milli Pascal-Seconds

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

ppm - Parts per Million

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

Flash point determination methods	Common name
---	-------------

ASTM D56.....	Tagliabue (Tag) closed cup
---------------	----------------------------

ASTM D92, DIN 51376, ISO 2592	Cleveland open cup
-------------------------------------	--------------------

ASTM D93, DIN 51758, ISO 2719	Pensky-Martens closed cup
-------------------------------------	---------------------------

ASTM D3278, DIN 55680, ISO 3679	Setaflash or Rapid closed cup
---------------------------------------	-------------------------------

DIN 51755.....	Abel-Pensky closed cup
----------------	------------------------

16.3 Conversion table:

Pressure:.....: 1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa

Viscosity:.....: 1 mPa*s = 1 centipoise (cP)