# SAFETY DATA SHEET

#### Material: 60002722 WACKER® AK 1 000 SILICONE FLUID Version 2.8 (US) Print Date 01/10/2024 Date of last alteration: 07/18/2023 Product and company identification 1. 1.1 Identification of the substance or preparation: Trade name WACKER® AK 1 000 SILICONE FLUID Use of the Substance/Mixture Industrial. Intermediate chemical 1.2 Company/undertaking identification: .....

Manufacturer/distributor:	Wacker Chemie AG Hanns-Seidel-Platz 4 81737 München Germany
Customer information:	Wacker Chemical Corporation 4950 S State Road Ann Arbor, MI 48108 InfoLine: Tel (517) 264-8240 Hours of operation: Monday - Friday, 8 am to 5 pm (eastern standard time) Corporate website: www.wacker.com
Emergency telephone no. (24h):	(517) 264-8500
Transportation emergency:	(800) 424-9300 (CHEMTREC, USA) (703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

# 2. Hazards identification

# 2.1 Classification of the substance or mixture

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200):

Not a hazardous substance or mixture.

# 2.2 Label elements

#### **GHS-Labelling:**

No labeling according to GHS required.

#### 2.3 Other hazards

No data available.

Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# 3. Composition/information on ingredients

# 3.1 Chemical characterization (substance)

CAS-No. Chemical characterization Polydimethylsiloxane

# 3.2 Information on ingredients:

This material does not contain any ingredients above the permitted limit(s).

# SAFETY DATA SHEET

# Material: 60002722

WACKER® AK 1 000 SILICONE FLUID

Version 2.8 (US)

Print Date 01/10/2024

Date of last alteration: 07/18/2023

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above  $\geq$  0.1%.

# 4. First-aid measures

#### 4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

#### 4.2 If inhaled

Material cannot be inhaled under normal conditions. No special treatment required.

#### 4.3 In case of skin contact

After skin contact wipe off excess material with cloth or paper. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

# 4.4 In case of eye contact

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

#### 4.5 If swallowed

No special measures are required after swallowing.

# 5. Fire-fighting measures

# 5.1 Flammable properties:

Property:	Value:	Method:
Flash point	257 °C (495 °F)	(ISO 2719)
Boiling point/boiling range	not determinable	(EU-GL.A.2)
Lower explosion limit	exempt	
Upper explosion limit	exempt	
Ignition temperature	410 °C (770 °F)	(EN 14522)
NFPA Hazard Class (comb./flam.liquid)	IIIB	

#### 5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

# 5.3 Recommended extinguishing media:

water-mist, carbon dioxide, sand, dry chemical or alcohol-resistant foam.

# 5.4 Unsuitable extinguishing media:

water-spray, sharp water jet.

# 5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide and incompletely burnt hydrocarbons .

#### 5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.

# SAFETY DATA SHEET

### Material: 60002722

WACKER® AK 1 000 SILICONE FLUID

Version 2.8 (US)

Print Date 01/10/2024

Date of last alteration: 07/18/2023

# 6. Accidental release measures

#### 6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

#### HAZWOPER PPE Level: D

#### 6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

#### 6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

# 7. Handling and storage

### 7.1 General information:

No special protective measures required.

#### 7.2 Handling

#### Precautions for safe handling:

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

#### Precautions against fire and explosion:

Observe the general rules for fire prevention.

# 7.3 Storage

#### Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

## Advice for storage of incompatible materials:

Observe local/state/federal regulations.

# Further information for storage:

Store in a dry and cool place.

Maximum temperature allowed during storage and transportation: 50 °C (122 °F)

A temporary increase in temperature during transport does not impair quality. Actively cooled transport guide can be dispensed with.

# 8. Exposure controls and personal protection

#### 8.1 Engineering controls

Ventilation:

Use with adequate ventilation.

Local exhaust:

No special ventilation required.

# 8.2 Associate substances with specific control parameters such as limit values

none known

# SAFETY DATA SHEET

## Material: 60002722

# WACKER® AK 1 000 SILICONE FLUID

Version 2.8 (US)

Print Date 01/10/2024

Date of last alteration: 07/18/2023

# 8.3 Personal protection equipment (PPE)

#### **Respiratory protection:**

Respiratory protection is not normally required.

# Hand protection:

Any liquid-tight rubber or vinyl gloves.

#### Eye protection:

Safety glasses with side shields or chemical safety goggles.

### Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

# 8.4 General hygiene and protection measures:

Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when handling. Follow standard industrial hygiene practices when using this material. Wash thoroughly after handling.

# 9. Physical and chemical properties

## 9.1 Appearance

9.2

9.3

Value:	Method:
-50 °C (-58 °F)	
not determinable	(EU-GL.A.2)
257 °C (495 °F)	(ISO 2719)
410 °C (770 °F)	(EN 14522)
exempt	
exempt	
exempt	
0.97 g/cm <sup>3</sup> at 25 °C (77 °F)	(DIN 51757)
practically insoluble at 20 °C (68 °F)	
Not applicable. Insoluble in water.	
no data available	
1000 mPa.s at 25 °C (77 °F)	(DIN 53019)
1000 mm²/s at 25 °C (77 °F)	(DIN 53019)
	257 °C (495 °F) 410 °C (770 °F) exempt exempt 0.97 g/cm <sup>3</sup> at 25 °C (77 °F) practically insoluble at 20 °C (68 °F) Not applicable. Insoluble in water. no data available 1000 mPa.s at 25 °C (77 °F)

No data available.

Odour Threshold:	no data available
Thermal decomposition:	> 250 °C (> 482 °F)

# 10. Stability and reactivity

# **10.1 General information:**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

#### 10.2 Conditions to avoid

None known.

# 10.3 Materials to avoid

None known.

# 10.4 Hazardous decomposition products

If stored and handled properly: none known. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150  $^{\circ}$ C (302  $^{\circ}$ F) through oxidation.

# SAFETY DATA SHEET

# Material: 60002722

# WACKER® AK 1 000 SILICONE FLUID

Version 2.8 (US)

Print Date 01/10/2024

Date of last alteration: 07/18/2023

# 10.5 Further information:

Hazardous polymerization cannot occur.

# 11. Toxicological information

# 11.1 Information on toxicological effects

# 11.1.1 Acute toxicity

# Product details:

Exposure routes	Result/Effect
Oral	LD50 > 5000 mg/kg
	Neither mortality nor clinical signs of toxicity were observed with the given dose.
	Species: Rat, Source: literature
dermal	LD50 > 2008 mg/kg
	Neither mortality nor clinical signs of toxicity were observed with the given dose.
	Species: Rat, Source: literature

# 11.1.2 Skin corrosion/irritation

# Product details:

No skin irritation	
(Species: Rabbit, Source: literature)	

### 11.1.3 Serious eye damage/eye irritation

#### Product details:

No eye irritation (Species: Rabbit, Source: literature)

# 11.1.4 Respiratory or skin sensitisation

# Product details:

Exposure routes	Result
Skin contact	Does not cause skin sensitisation.
	(Species: Guinea pig, Test system: Maximisation Test, Method: OECD 406, Source: literature)
Inhalation	No data available.

# 11.1.5 Germ cell mutagenicity

#### Assessment:

Based on known data a significant mutagenic potential may be excluded.

negative

(Test system: mutation assay (in vitro) / bacterial cells, Method: OECD 471, Source: literature)

# 11.1.6 Carcinogenicity

# Assessment:

Animal tests have not revealed any carcinogenic effects.

# Product details:

NOAEL: >= 1000 mg/kg

NOAEL= NOAEL (carcinogenic effects)

(Test system: carcinogenicity study, Species: Rat, Strain: Fischer F344, Application Route: Oral, Route of administration: feed, Test period: 2 a, Test substance: Polydimethylsiloxane, Source: literature)

# 11.1.7 Reproductive toxicity

# Assessment:

Animal tests have shown no indications of possibility of damage to embryo and impairment of fertility.

# SAFETY DATA SHEET

# Material: 60002722

WACKER® AK 1 000 SILICONE FLUID

Version 2.8 (US)

Print Date 01/10/2024

Date of last alteration: 07/18/2023

#### Product details:

Reproductive Toxicity/Development/Teratogenicity

NOAEL (developmental): >= 1000 mg/kg

NOAEL (maternal): >= 1000 mg/kg

(Symptoms/Effect: Nothing abnormal detected., Test system: Developmental Toxicity Study, Species: Rabbit, Application Route: Oral, Route of administration: gavage, Frequency of Treatment: day 6 - 19 of gestation, Test substance: Polydimethylsiloxane, Source: literature)

# 11.1.8 Specific target organ toxicity - single exposure

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

#### 11.1.9 Specific target organ toxicity - repeated exposure

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

#### Product details:

Result/Effect NOAEL: >= 1000 mg/kg NOAEL = NOAEL (systemic effects) (Test system: chronic study, Species: Rat, Application Route: Oral, Route of administration: feed, Test period: 1 a, Subsequent observation period: 1 a, Source: literature)

## 11.1.10 Aspiration hazard

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

#### **11.1.11 Endocrine disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# 11.1.12 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other information: Human patch test: Product displays good compatibility with the skin.

# 12. Ecological information

#### 12.1 Toxicity

#### Assessment:

Evaluation on basis of physical-chemical properties: No expected damaging effects to aquatic organisms.

# Product details:

Result/Effect	Species/Test system	Source
LL50: > 1000 mg/l (nominal)	static test	literature
The effect level is greater than the maximum achievable	Fish (96 h)	
concentration. The value refers to the water-		
accommodated fraction (WAF).		
EC50: > 0.0001 mg/l (measured)		literature
The effect level is greater than the maximum achievable	Daphnia magna (Water flea) (48 h)	
concentration. The value refers to the water-		
accommodated fraction (WAF).		



# SAFETY DATA SHEET

# Material: 60002722

#### WACKER® AK 1 000 SILICONE FLUID

Version 2.8 (US)

# Print Date 01/10/2024

Date of last alteration: 07/18/2023

IC50 (Growth rate): > 100000 mg/l (nominal) The effect level is greater than the maximum achievab concentration. The value refers to the water- accommodated fraction (WAF).	static test le Skeletonema costatum (marine diatom) (72 h)	literature
NOEC: > 10000 mg/kg	feeding study Oncorhynchus mykiss (rainbow trout) (28 d)	literature
NOEC (mortality): > 500 mg/kg The exposure to treated sediment did not result in effects.	exposure via sediment Daphnia magna (Water flea) (21 d)	literature
NOEC (Growth): > 500 mg/kg The exposure to treated sediment did not result in effects.	exposure via sediment Daphnia magna (Water flea) (21 d)	literature
NOEC (reproduction rate): > 500 mg/kg The exposure to treated sediment did not result in effects.	exposure via sediment Daphnia magna (Water flea) (21 d)	literature

# 12.2 Persistence and degradability

#### Assessment:

Polymer component: biologically not degradable. Elimination by adsorption to activated sludge.

#### 12.3 Bioaccumulative potential

# Assessment:

Polymer component: No adverse effects expected.

#### 12.4 Mobility in soil

#### Assessment:

Polymer component: insoluble in water.

# 12.5 Results of PBT and vPvB assessment

No data available.

#### 12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

none known

# 13. Disposal considerations

# 13.1 Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

# 13.2 Packaging disposal

#### Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

# 14. Transport information

# 14.1 US DOT & CANADA TDG SURFACE

Valuation ..... Not regulated for transport

# SAFETY DATA SHEET

# Material: 60002722

# WACKER® AK 1 000 SILICONE FLUID

Version 2.8 (US) Print Date 01/10/2024 Date of last alteration: 07/18/2023

 Interview
 Print Date 01/10/2024

 Version 2.8 (US)
 Print Date 01/10/2024
 Date of last alteration: 07/18/2023

 Interview
 Interview

# 14.3 Air transport ICAO-TI/IATA-DGR

Valuation ...... Not regulated for transport

# 15. Regulatory information

# 15.1 U.S. Federal regulations

#### **TSCA** inventory status and **TSCA** information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

#### TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

#### **CERCLA Regulated Chemicals:**

This material does not contain any CERCLA regulated chemicals.

#### SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

# SARA 311/312 Hazard Class:

No SARA Hazards

#### SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

#### HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

#### 15.2 US State Regulations

#### US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer.

This material does not contain any chemicals known to the State of California to cause reproductive effects.

### Massachusetts Substance List:

This material contains no listed components.

#### Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

#### 15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan	<b>ENCS</b> (Handbook of Existing and New Chemical Substances):
	This product is listed in, or complies with, the substance inventory.
Australia:	AIIC (Australian Inventory of Industrial Chemicals):
	This product is listed in, or complies with, the substance inventory.
China:	<b>IECSC</b> (Inventory of Existing Chemical Substances in China):
	This product is listed in, or complies with, the substance inventory.
Canada:	DSL (Domestic Substance List):
	This product is listed in, or complies with, the substance inventory.
Philippines:	<b>PICCS</b> (Philippine Inventory of Chemicals and Chemical Substances):
	This product is listed in, or complies with, the substance inventory.
United States of America (USA):	<b>TSCA</b> (Toxic Substance Control Act Chemical Substance Inventory):
	All components of this product are listed as active or are in compliance with the
	substance inventory.

# SAFETY DATA SHEET

Material: 60002722	WACKER® AK 1 000 SILICONE FLUID	
Version 2.8 (US)	Print Date 01/10/2024	Date of last alteration: 07/18/2023
Taiwan	This product is listed in, or complies wit The Taiwanese chemicals regulation re or TCSI-compliant substances if import exceed the trigger quantity of 100 kg/a	th, the substance inventory. General note: equires a phase 1 registration for TCSI-listed is to Taiwan or manufacturing in Taiwan
European Economic Area (EEA).	manufactured within the EEA by the su	ns for substances imported into the EEA or pplier mentioned in section 1 are fulfilled by ations for substances imported into the EEA
South Korea (Republic of Korea)	: <b>AREC</b> (Act on Registration and Evaluar Please approach your regular contact for	tion of Chemicals; "K-REACH"):

# 16. Other information

# 16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

# 16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists DOT - Department of Transportation hPa - Hectopascals mPa*s - Milli Pascal-Seconds OSHA - Occupational Safety and Health Administration PEL - Permissible Exposure Limit	ppm - Parts per Million SARA - Superfund Amendments and Reauthorization Act STEL - Short Term Exposure Limit TSCA - Toxic Substances Control Act TWA - Time Weighted Average
Flash point determination methods ASTM D56	
ASTM D92, DIN 51376, ISO 2592	5 ( 5)
ASTM D93, DIN 51758, ISO 2719	Pensky-Martens closed cup
ASTM D3278, DIN 55680, ISO 3679	Setaflash or Rapid closed cup

# 16.3 Conversion table:

Pressure:	1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa
Viscosity:	1 mPa*s = 1 centipoise (cP)

DIN 51755..... Abel-Pensky closed cup