

Material: 60002675 WACKER® AK 35 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

1. Product and company identification

1.1 Identification of the substance or preparation:

Trade name WACKER® AK 35
SILICONE FLUID

Use of the Substance/Mixture Industrial.

Intermediate chemical

1.2 Company/undertaking identification:

Manufacturer/distributor: Wacker Chemie AG

Gisela-Stein-Straße 1 81671 München Germany

Customer information: Wacker Chemical Corporation

4950 S State Road Ann Arbor, MI 48108

InfoLine:

Tel (517) 264-8240 Hours of operation:

Monday - Friday, 8 am to 5 pm (eastern standard time)

Corporate website: www.wacker.com

Emergency telephone no. (24h): (517) 264-8500

Transportation emergency: (800) 424-9300 (CHEMTREC, USA)

(703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (GHS):

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (GHS):

No labeling according to GHS required.

2.3 Other hazards

No data available.

Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Composition/information on ingredients

3.1 Chemical characterization (substance)

CAS-No.	Chemical characterization
	Polydimethylsiloxane

3.2 Information on ingredients:

This material does not contain any ingredients above the permitted limit(s).



WACKER® AK 35 Material: 60002675 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for noncarcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

First-aid measures

- 4.1 **General information:**
- 4.2 If inhaled
- 4.3 In case of skin contact
- 4.4 In case of eve contact
- 4.5 If swallowed

5. Fire-fighting measures

5.1 Flammable properties:

	Property:	Value:	Method:
	Flash point	> 120 °C (> 248 °F)	(EN 22719)
	Flash point	> 205 °C (> 401 °F)	(ISO 2719)
	Boiling point/boiling range	400 °C (752 °F) at 1013 hPa	(EU-GL.A.2)
-	Lower explosion limit		
	Upper explosion limit	exempt	
	Ignition temperature	390 °C (734 °F)	(EN 14522)

5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

5.3 Recommended extinguishing media:

water-mist, carbon dioxide, sand, dry chemical or alcohol-resistant foam.

5.4 Unsuitable extinguishing media:

water-spray, sharp water jet.

- 5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases not applicable
- 5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with

6. Accidental release measures

6.1 **Precautions:**

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: D

6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.



Material: 60002675 WACKER® AK 35 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

7. Handling and storage

7.1 General information:

No special protective measures required.

7.2 Handling

Precautions for safe handling:

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

Precautions against fire and explosion:

Observe the general rules for fire prevention.

7.3 Storage

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place.

Maximum temperature allowed during storage and transportation: 50 °C (122 °F)

A temporary increase in temperature during transport does not impair quality. Actively cooled transport guide can be dispensed with.

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use with adequate ventilation.

Local exhaust:

No special ventilation required.

8.2 Associate substances with specific control parameters such as limit values

not applicable

8.3 Personal protection equipment (PPE)

Respiratory protection:

Respiratory protection is not normally required.

Hand protection:

Any liquid-tight rubber or vinyl gloves.

Eye protection:

Safety glasses with side shields or chemical safety goggles.

Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.



WACKER® AK 35 Material: 60002675 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

8.4 General hygiene and protection measures:

Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when handling. Follow standard industrial hygiene practices when using this material. Wash thoroughly after handling.

Physical and chemical properties

9.1 **Appearance**

Physical state: liquid

Colour colorless transparent

Odour: odourless

9.2 Safety data

	Property:	Value:	Method:
	Melting point	-60 °C (-76 °F)	
	Boiling point/boiling range	400 °C (752 °F) at 1013 hPa	(EU-GL.A.2)
	Flash point		(EN 22719)
	Flash point	> 205 °C (> 401 °F)	(ISO 2719)
	Ignition temperature	390 °C (734 °F)	(EN 14522)
	Lower explosion limit		· ·
	Upper explosion limit	exempt	
	Vapour pressure	< 0.1 hPa / 20 °C (68 °F)	
-	Density:	0.96 g/cm3 at 25 °C (77 °F)	(DIN 51757)
	Water solubility:	practically insoluble	
	pH	Not applicable. Insoluble in water.	
	Partition coefficient: n-octanol/water	no data available	
	Viscosity, dynamic	31 - 39 mPa.s at 25 °C (77 °F)	(DIN 53019)
=	Viscosity, kinematic	35 mm ² /s at 25 °C (77 °F)	(DIN 53019)
0.3	Further information		

Further information 9.3

No data available.

Odour Threshold: no data available Thermal decomposition...... > 250 °C (> 482 °F)

10. Stability and reactivity

General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

None known.

10.3 Materials to avoid

None known.

Hazardous decomposition products 10.4

If stored and handled properly: none known. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

Further information: 10.5

Hazardous polymerization cannot occur.

11. **Toxicological information**

Information on toxicological effects

11.1.1 Acute toxicity



Material: 60002675 WACKER® AK 35 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

Product details:

Exposure routes	Result/Effect
Oral	LD50 > 5000 mg/kg
	Neither mortality nor clinical signs of toxicity were observed with the given dose.
	Species: Rat, Source: literature
dermal	LD50 > 2008 mg/kg
	Neither mortality nor clinical signs of toxicity were observed with the given dose.
	Species: Rat, Source: literature

11.1.2 Skin corrosion/irritation

Product details:

No skin irritation

(Species: Rabbit, Source: literature)

11.1.3 Serious eye damage/eye irritation

Product details:

No eye irritation

(Species: Rabbit, Source: literature)

11.1.4 Respiratory or skin sensitisation

Product details:

Exposure routes	Result
Skin contact	Does not cause skin sensitisation.
	(Species: Guinea pig, Test system: Maximisation Test, Method: OECD 406, Source: literature)
Inhalation	No data available.

11.1.5 Germ cell mutagenicity

Assessment:

Based on known data a significant mutagenic potential may be excluded.

negative

(Test system: mutation assay (in vitro) / bacterial cells, Method: OECD 471, Source: literature)

11.1.6 Carcinogenicity

Assessment:

Animal tests have not revealed any carcinogenic effects.

Product details:

NOAEL: >= 1000 mg/kg

NOAEL= NOAEL (carcinogenic effects)

(Test system: carcinogenicity study, Species: Rat, Strain: Fischer F344, Application Route: Oral, Route of administration: feed, Test period: 2 a, Test substance: Polydimethylsiloxane, Source: literature)

11.1.7 Reproductive toxicity

Assessment:

Animal tests have shown no indications of possibility of damage to embryo and impairment of fertility.

Product details:

Reproductive Toxicity/Development/Teratogenicity

NOAEL (developmental): >= 1000 mg/kg

NOAEL (maternal): >= 1000 mg/kg

(Symptoms/Effect: Nothing abnormal detected., Test system: Developmental Toxicity Study, Species: Rabbit, Application Route: Oral, Route of administration: gavage, Frequency of Treatment: day 6 - 19 of gestation, Test substance: Polydimethylsiloxane, Source: literature)



Material: 60002675 WACKER® AK 35 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

11.1.8 Specific target organ toxicity - single exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity - repeated exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Product details:

Result/Effect

NOAEL: >= 1000 mg/kg

NOAEL = NOAEL (systemic effects)

(Test system: chronic study, Species: Rat, Application Route: Oral, Route of administration: feed, Test period: 1 a, Subsequent

observation period: 1 a, Source: literature)

11.1.10 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.11 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

11.1.12 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other information: Human patch test: Product displays good compatibility with the skin.

12. Ecological information

12.1 Toxicity

Assessment:

Evaluation on basis of physical-chemical properties: No expected damaging effects to aquatic organisms.

Product details:

Result/Effect	Species/Test system	Source
LL50: > 1000 mg/l (nominal)	static test	literature
The effect level is greater than the maximum achievable	Fish (96 h)	
concentration. The value refers to the water-		
accommodated fraction (WAF).		
EC50: > 0.0001 mg/l (measured)	static test	literature
The effect level is greater than the maximum achievable	Daphnia magna (Water flea) (48 h)	
concentration. The value refers to the water-		
accommodated fraction (WAF).		
IC50 (Growth rate): > 100000 mg/l (nominal)	static test	literature
The effect level is greater than the maximum achievable	Skeletonema costatum (marine diatom) (72 h)	
concentration. The value refers to the water-		
accommodated fraction (WAF).		
NOEC: > 10000 mg/kg	feeding study	literature
	Oncorhynchus mykiss (rainbow trout) (28 d)	
NOEC (mortality): > 500 mg/kg	exposure via sediment	literature
The exposure to treated sediment did not result in	Daphnia magna (Water flea) (21 d)	
effects.		



Material: 60002675 WACKER® AK 35 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

NOEC (Growth): > 500 mg/kg The exposure to treated sediment did not result in effects.	exposure via sediment Daphnia magna (Water flea) (21 d)	literature
NOEC (reproduction rate): > 500 mg/kg	exposure via sediment	literature
The exposure to treated sediment did not result in effects.	Daphnia magna (Water flea) (21 d)	

12.2 Persistence and degradability

Assessment:

Polymer component: biologically not degradable. Elimination by adsorption to activated sludge.

12.3 Bioaccumulative potential

Assessment:

Polymer component: No adverse effects expected.

12.4 Mobility in soil

Assessment:

Polymer component: insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

none known

13. Disposal considerations

13.1 Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation Not regulated for transport

14.2 Transport by sea IMDG-Code

Valuation Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation Not regulated for transport

15. Regulatory information



WACKER® AK 35 Material: 60002675 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

15.1 U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

No SARA Hazards

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

15.2 U.S. State regulations

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This material does not contain any chemicals known to the State of California to cause cancer.

This material does not contain any chemicals known to the State of California to cause reproductive effects.

Massachusetts Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan ENCS (Handbook of Existing and New Chemical Substances): This product is listed in, or complies with, the substance inventory. This product is listed in, or complies with, the substance inventory. China...... IECSC (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory. Canada : DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory. This product is listed in, or complies with, the substance inventory. United States of America (USA)...... TSCA (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.

TCSI (Taiwan Chemical Substance Inventory):

This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of

this obligation.

European Economic Area (EEA)...... REACH (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.



Material: 60002675 WACKER® AK 35 SILICONE FLUID

Version 2.8 (US) Print Date 09/23/2025 Date of last alteration: 04/07/2023

South Korea (Republic of Korea): AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"):

Please approach your regular contact for more detailed information.

16. Other information

16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial

Hygienists

DOT - Department of Transportation

hPa - Hectopascals

mPa*s - Milli Pascal-Seconds

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

ppm - Parts per Million

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

Flash point determination methods Common name

16.3 Conversion table:

Pressure:...... 1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa

Viscosity: 1 mPa*s = 1 centipoise (cP)