



Item No: WR2N
2-Channel Power Unit, 200 W (300 W)

RECOMMENDED FOR FOLLOWING APPLICATIONS

KEY FEATURES

TECHNICAL DATA

Equipotential bonding	✓
ESD-safe	✓
Vacuum	0, 7 bar
WT compatible	✓
Max. hot air flow rate l/min (depends on tool)	10
Channels	2
Max. vacuum	0,7 bar
Voltage	120 V
Power	250 W (300 W)
Temperature accuracy °F	±17
Temperature stability °F	±4
Temperature range	93, 3333° C to 454, 444° C
IPC-compliant	Soldering tip (tip to ground) corresponds to IPC-J-001
Temperature accuracy °C	±9

Overcurrent release	1,6 A
Display	LCD
Temperature range	Temperature control of channels Soldering and desoldering iron stepless 50 °C – 550 °C (150 °F – 999 °F) Controllable temperature range depends on the tool. WP 80 / WP 120 50 °C-450 °C (150 °F-850 °F) WSP 150 50 °C-550 °C (150 °F-950 °F) WP 200 50 °C-550 °C (150 °F-950 °F) WMRT / WMRP 100 °C-450 °C (200 °F-850 °F) DSX 80 / DXV 80 50 °C-450 °C (150 °F-850 °F) DSX 120 50 °C-450 °C (150 °F-850 °F) HAP 200 / HAP 1 50 °C-550 °C (150 °F-999 °F)
Temperature stability °C	±2
Temperature range °F	200°F to 850°F
Dimensions L x W x H (Inches)	11,02 x 9,45 x 4,06
Weight (approx.) in kg	5.6
Capacity l/min	18