



## WT 1010M 1 CHANNEL MICRO SOLDERING KIT, 95 W, 120 V

ORDER NO: WT1010M

COMPACT. POWERFUL. VERSATILE.  
BOOST YOUR PRODUCTIVITY

### Discover the WT 1M Soldering Station, your ultimate productivity partner.

With extremely fast heat-up and recovery times, it handles all tasks effortlessly. No more juggling tools or compromising performance – just reliable versatility and unmatched value. Choose worry-free precision and unstoppable productivity. Choose Weller WT Soldering Stations.

## + KEY FEATURES

- > **1 CHANNEL MICRO SOLDERING KIT (95 W)**  
to cover micro and standard soldering tasks including  
WTMP MS Micro pencil with active (cartridge) tip technology
- > **RTM TIP FAMILY**  
with 5 seconds heat-up time
- > **HIGH PRODUCTIVITY**
- > **INTUITIVE USE**  
thanks to clear menu structure
- > **REDUCED FOOTPRINT**  
thanks to stackability
- > **GRAPHICAL BACKLIT LC-DISPLAY**
- > **HIGH PERFORMANCE AND FUNCTIONALITY**  
many connectable tools
- > **HOUSING COVER**  
useable as storage
- > **OFF TIME, PROCESS WINDOW,**  
Lock function, Offset
- > **STACKABLE UNITS**  
useable as storage
- > **CONNECTABLE TO**  
ZeroSmog Fume Extraction Units
- > **ESD-SAFE** 

SCOPE OF SUPPLY
WT1M Power Unit, 120V WTMP MS Soldering Iron, 12V RTM 013 S MS Micro Soldering Tip WSR 205 Safety Rest with Stop & Go Function

TECHNICAL DATA SOLDERING STATION WT 1010M
<b>Dimensions L x W x H (mm)</b> 150 x 130 x 101 <b>Dimensions L x W x H (inch)</b> 5.91 x 5.12 x 3.98
<b>Fuse</b> 120V (mA) T1
<b>Weight approx. (kg)</b> 1,9
<b>Mains supply voltage (V/Hz)</b> 120 / 50
<b>Power consumption (W)</b> 95
<b>Safety class</b> I, antistatic housing III, Soldering tool
<b>Temperature range / Tool dependent</b> °C 50 - 450 / 550
<b>Temperature accuracy</b> °C ± 9 / ± 17
<b>Temperature stability</b> °C ± 2
<b>Subject to technical alterations and amendments.</b>

TECHNICAL DATA SOLDERING IRON WTMP MS
<b>Temperature range</b> °C 100 - 450 <b>Temperature range</b> °F 150 - 950
<b>Power consumption (W)</b> 40W (55W)
<b>Mains supply voltage (V/Hz)</b> 12V / AC
<b>Heat-up time (50°C to 350°C) (120°F to 660°F)</b> 5 sec.
<b>Safety rest</b> WSR 205
<b>Tip type series</b> RTM MS
<b>Supply unit</b> WT 1M, WT 2M, WR 3M
<b>Subject to technical alterations and amendments.</b>

#PowerfulTogether



[More information](#)