## Kraftform Kompakt VDE











**EAN:** 4013288220851 **Size:** 230x60x12 mm

Part number:05004406001Weight:28 gArticle number:Kraftform Kompakt VDE 60Country of origin:CZ

iS SB

Customs tariff number:

82041100

- Reduced shaft diameter and integrated insulation protection
- This means that low-lying screws and spring elements can be accessed and actuated
- Insulated, individually tested as per IEC 60900
- 9 mm hex drive with lead-in chamfer
- The Wera Black Point tip offers an exact fit and optimum corrosion protection

Interchangeable blade with reduced shaft diameter and integrated insulation protection; this means that low-lying screws and spring elements can be accessed and actuated. Individual testing at 10,000 volts so as to ensure safe working at the permitted voltage of 1,000 volts.

Web link

 $https://products.wera.de/en/tools\_for\_electricians\_kraftform\_kompakt\_vde\_kraftform\_kompakt\_vde\_60\_is\_sb.html$ 

## Kraftform Kompakt VDE



### Set contents:



**KK 60 iS** 05003406001

1 x 0.6 x 3.5 x 154 mm

## Individually tested




Kraftform Kompakt VDE sets come with an insulated handle and insulated inter-changeable blades, that can be exchanged without any special tools.

# kV kV

Our screwdrivers are tested for dielectric strength under a 10,000 volt load to make sure that their most important property, their insulation, has been exhaustively tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.

# VDE interchangeable blade with reduced shaft diameter




Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900.

# VDE interchangeable blades 154 mm long



Suitable for Kraftform handles 7400 VDE, 827 T i and 817 VDE .

# Handle/interchangeable blade system – Kraftform Kompakt VDE



The handle/interchangeable blade system allows rapid exchange of the blades required for a wide range of applications.