



<b>EAN:</b>	4013288095398	<b>Size:</b>	50x16x2 mm
<b>Part number:</b>	05027202001	<b>Weight:</b>	2 g
<b>Article number:</b>	950 BM	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82041100

- L-keys for hexagonal socket screws
- L-keys with Hex-Plus advantage for a longer screw life
- Laser-engraved and thereby wear-resistant size markings
- BlackLaser for high corrosion protection and long service life
- Metric

High quality L-keys for hexagonal socket screws. Hex-Plus offers a larger contact surface within the screw head. This reduces the notching effects to a minimum and almost completely eliminates the risk of destroying the screw recess. The BlackLaser surface treatment provides outstanding surface protection, even against corrosion, and a long service life. Wear-resistant size markings for rapid accessing.

**Web link**

[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_bm.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_bm.html)

Wera - 950 BM  
05027202001 - 4013288095398

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## L-Keys for Hexagon Socket Screws

### L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

### Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

### Size identification



The size of each L-keys has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

### Surface protection



L-keys with BlackLaser surface treatment for outstanding surface protection and long service life. High corrosion protection.

### Web link






[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_bm.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_bm.html)

Wera - 950 BM  
05027202001 - 4013288095398

Wera Werkzeuge GmbH  
Korzer Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## L-Keys for Hexagon Socket Screws

Further versions in this product family:

					
	mm	mm	mm	inch	inch
05027201001 <sup>1)</sup>	1.5	45	14	1 3/4	9/16
<b>05027202001</b>	<b>2.0</b>	<b>50</b>	<b>16</b>	<b>2</b>	<b>5/8</b>
05027203001	2.5	56	18	2 7/32	23/32
05027204001	3.0	63	20	2 1/2	25/32
05027205001	3.5	66	23	2 5/8	29/32
05027206001	4.0	70	25	2 3/4	1
05027207001	4.5	75	26	3	1 1/32
05027208001	5.0	80	28	3 1/8	1 3/32
05027209001	6.0	90	32	3 1/2	1 1/4
05027210001	7.0	95	34	3 3/4	1 5/16
05027211001	8.0	100	36	4	1 7/16
05027213001	9.0	106	38	4 11/64	1 1/2
05027212001	10.0	112	40	4 7/16	1 9/16
05027214001	11.0	120	43	4 23/32	1 11/16
05027215001	12.0	125	45	5	1 49/64

1) Regular hexagon

## Web link

[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_bm.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_bm.html)

Wera - 950 BM

05027202001 - 4013288095398

Wera Werkzeuge GmbH

Korzerter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: [info@wera.de](mailto:info@wera.de)