Size:

Weight:

Country of origin:

ESD-safe Micro screwdriver. Dependable protection against electrostatic energy and associated damage. Rapid twisting results from fixing the hand on the head and using the fast-turning zone just below. This makes time-consuming grip adjustments unnecessary. Power zones with integrated soft sections ensure the transfer of high loosening and tightening torque; a precision zone for the right rotation angle during fine adjustment work. The Black Point tip offers optimised corrosion protection and an exact fit. "Take it easy" tool

finder with colour coding according to profiles and size stamp - for simple and rapid accessing of the required tool.

Customs tariff number:

138x19x19 mm

12 g

CZ

82054000

4013288194763

1578 A ESD Micro

05030108001

Kraftform Micro screwdriver for slotted screws

· Anti-roll feature and swivel cap for rapid twisting

• ESD-safe tool thanks to surface resistance of $\leq 10^{9}$ Ohm

• Take it easy tool finder: colour coding according to profile and size

 Multi-component Kraftform Micro handle for fast and ergonomic screwdriving • The Wera Black Point tip offers an exact fit and optimum corrosion protection

ESD Series

EAN:

Part number:

Article number:





















Wera - 1578 A ESD Micro 05030108001 - 4013288194763

ESD Series

Wera ESD Tools



The requirements for ESD-safe screwdrivers are specified in the European standard DIN EN 61340-5-1. This standard also includes a handle that has to be out of a defined conductive material. The Wera products in the ESD series satisfy these standards and the even more stringent requirements demanded by some technology companies.

High protection






Multi-component screwdriver handle for ergonomic working.

The precision zone



The precision zone directly above the blade gives the user a better feel for the right rotation angle during fine adjustment work.

The power zone



The power zone has integrated soft zones near the blade tip to ensure high torque transfer for loosening or tightening screws without losing contact with the screw.

Rotating cap and fast-turning zone

0 0

The electric surface resistance of

the Wera ESD material is $\leq 10^{9}$

ohm. This securely protects

components against electrostatic

energy and associated damage.



The fast-turning zone just below the rotating cap allow rapid twisting. This makes timeconsuming grip adjustments as with other conventional precision screwdrivers unnecessary.

"Take it easy" Tool Finder



Screwdrivers with "Take it easy" tool finder: colour coding according to profile and size stamp.

Wera Black Point tip



The Wera Black Point tip and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.



ESD Series

Further versions in this product family:

			↓ ▼		Ø		
	mm	mm	mm	mm	mm	inch	inch
05030099001	0.16	0.8	40	97	2.0	1/32	1 9/16
05030101001	0.23	1.5	40	97	2.0	1/16	1 9/16
05030100001	0.25	1.2	40	97	2.0	0.05	1 9/16
05030102001	0.30	1.8	60	97	2.0	0.07	2 3/8
05030108001	0.35	2.5	40	97	2.5	3/32	1 9/16
05030103001	0.40	2.0	60	97	2.5	5/64	2 3/8
05030104001	0.40	2.5	80	97	2.5	3/32	3 1/8
05030105001	0.50	3.0	80	97	3.0	1/8	3 1/8
05030106001	0.60	3.5	80	97	4.0	9/64	3 1/8
05030107001	0.80	4.0	80	97	4.0	5/32	3 1/8