

950/9 Hex-Plus 6 SB L-key set, metric, BlackLaser, 9 pieces

L-Keys for Hexagon Socket Screws



EAN:	4013288106414	Size:	245x95x30 mm
Part number:	05073596001	Weight:	479 g
Article number:	950/9 Hex-Plus 6 SB SiS	Country of origin:	CZ
		Customs tariff number:	82054000

- In a practical clip out of wear-free material
- Hex-Plus allows socket head screws to live longer
- BlackLaser for high corrosion protection and long service life
- Laser-engraved and thereby wear-resistant size markings on the L-keys
- In a practical clip out of wear-free material

High quality L-key set for hexagonal socket screws in a practical clip fastener out of wear-resistant material, enabling secure storage of the L-keys as well as simple removal. L-keys with Hex-Plus profile: offers a larger contact surface within the screw head. This reduces the notching effects to a minimum and almost completely eliminates the risk of destroying the screw recess. The ball-end on the long arm allows for reliable working even in difficult installation situations. The BlackLaser surface treatment provides outstanding surface protection, even against corrosion, and a long service life. The tools are quickly to hand thanks to the laser-engraved and thereby wear-resistant size markings on the L-keys.

Web link

https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_9_hex-plus_6_sb_sis.html

Wera - 950/9 Hex-Plus 6 SB SiS
05073596001 - 4013288106414

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

L-Keys for Hexagon Socket Screws

Set contents:

950 PKL BM L-key, metric, BlackLaser, 1.5 x 90 mm



05027101001 ¹⁾	1x	1.5 x 90 mm
05027102001	1x	2 x 100 mm
05027103001	1x	2.5 x 112 mm
05027104001	1x	3 x 126 mm
05027105001	1x	4 x 140 mm
05027106001	1x	5 x 160 mm
05027107001	1x	6 x 180 mm
05027108001	1x	8 x 200 mm
05027109001	1x	10 x 219 mm

1) Regular hexagon

L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

Size identification



The size of each L-keys has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

Web link

https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_9_hex-plus_6_sb_sis.html

Wera - 950/9 Hex-Plus 6 SB SiS
05073596001 - 4013288106414

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

L-Keys for Hexagon Socket Screws

Surface protection



L-keys with BlackLaser surface treatment for outstanding surface protection and long service life. High corrosion protection.

Secure hold and easy removal



The wear-resistant clip material ensures that the L-keys are securely held yet are easy to remove.

Web link

https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_9_hex-plus_6_sb_sis.html

Wera - 950/9 Hex-Plus 6 SB SiS
05073596001 - 4013288106414

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de