

Programmable Refrigerated Eco Incubator



Forced Air Convection

INE800-115V / INE800-220V

Temperature range 0~+60°C

Temp. distribution accuracy $\pm 0.5^{\circ}\text{C}$ (at 37°C during continuous operation)

Internal capacity 286L

Inverter control Energy savings




Upgraded inverter control improved refrigeration efficiency, reduced frost significantly and minimized wasted power during refrigeration.

- 44% power savings compared to previous models
- Controller upgraded for easier viewing and operability
- Temperature distribution accuracy improved for better incubation
- Standard equipped with program operation, auto-stop, auto-start, self-diagnostic, timer, calibration off-set, memory, and electricity & CO₂ emission monitor
- Designed with Analog Output (4-20mA) and External Communication Port (RS485)

Specifications

Model	INE800-115V	INE800-220V
System	Forced air convection	
Operating temperature range	0~+60°C	
Setting temperature range	-5~+65°C	
Temperature adjustment accuracy	$\pm 0.2^{\circ}\text{C}$ (at 37°C during continuous operation), $\pm 0.5^{\circ}\text{C}$ (at 37°C cycle operation)	
Temperature fluctuation	$\pm 0.3^{\circ}\text{C}$ (at 37°C during continuous operation), $\pm 1.0^{\circ}\text{C}$ (at 37°C cycle operation)	
Temperature distribution accuracy	$\pm 0.5^{\circ}\text{C}$ (at 37°C during continuous operation)	
Temperature gradient	2.0°C (at 37°C during continuous operation)	
Max. temperature reaching time	20~60°C 35min.	
Min. temperature reaching time	20~0°C 50min.	
Cooling Mechanism	Continuous operation, Cycle operation, Cooling-stop operation	
Interior	Stainless steel	
Exterior	Chromate-free electrogalvanized steel plate Baked chemical resistant finish	
Heat insulator	Styrene foam (non-freon)	
Freezer	200W Rotary Unit	
Cooling Medium	R134a 350g	
Operation range of freezer	Below 40°C	
Defrosting mechanism	Hot Gas Bypass Method, Manual (random) Defrost / Auto (time) Defrost	
Blower fan	DC Axial flow fan 4-Step, Equipped with Error Signal when stopped	
Heater	Iron-chrome wire heater : 750W	
Sensor	Double sensor: Platinum resistance temperature detector: Pt100Ω (temperature controller), K-thermocouple (overheat prevention device)	
Cable port	I.D.: 50 mm (right side of main unit)	
Temperature controller	PID control by microprocessor	
Temperature Display	Setting Temp. Display : 5-digit orange LED digital display, Actual Temp. Display : 4-digit green LED digital display	
Timer / timer resolution	0~99hr. 59min. / 1min.	
Operation function	Fixed temperature, Auto start, Auto stop, Quick auto stop, Program (99 steps, 99 patterns)	
Additional function	Timer, Calibration off-set, Electricity & CO ₂ Emission Monitor, Voltage Recovery Optional, User Setting saving/readout, Calendar timer (24 hours)	
Safety device	Self diagnostic function (temp. sensor error, heater disconnection, SSR short-circuit, main relay error, automatic overheat prevention), Key lock, Overcurrent electric leakage breaker, Overheat prevention device, Fan malfunction detector, Cooling high-pressure detector, Inverter malfunction detector	
External dimensions	W710 x D645 x H1730mm	
Internal dimensions	W600 x D477 x H1000 (effective 800) mm	
Internal capacity	286L	
Shelf load capacity	15 kg/pc.	
Shelf rest step number / pitch	23 steps / 30mm	
Power supply (50/60 Hz)	AC115V 8.7A	AC220V 4.5A
Weight	~135kg	
Included accessories	Stainless steel punched metal 5 pcs. shelf / 10pcs. brackets, 2 keys, silicon stopper for cable hole 1 pc	

Power Consumption Comparison




	0°C	3°C	20°C	37°C
IN804	648	712	864	1007
INE800	409	446	498	560
Reduction Rate	37%	37%	42%	44%

Comparison with IN804

- Condition : AC115V/50Hz, Room Temp 23°C, 5 shelves, no load
- Data was taken when each setting was stable

CO₂ emissions reduced by approx 1,269 kg
(Calculated for 1 year operation with 37°C setting)

Falling / Rising Temp. Curve




9 Point Temperature Distribution


	Upper Front Left	Upper Back Left	Upper Front Right	Upper Back Right	Lower Front Left	Lower Back Left	Lower Front Right	Lower Back Right	Center Side	(°C)
No load	37.1	36.2	37.2	36.9	36.8	36.8	37.1	36.9	37.0	
Loaded	37.1	36.3	37.0	36.9	36.5	35.9	36.7	36.1	37.0	

Condition

- Above 9 measurement points were taken from the effective internal capacity down-scale by 10% (as the image on the right)
- Room Temp. 23°C, AC115V, 50Hz, Average temperature during stable setting temp. set at 37°C
- No Load condition: 5 shelves
- Loaded condition: each of the 12 shelves were loaded with 20 Petri Dishes (Total : 240 Petri Dishes)



Method



Control Panel



Overheat Prevention Device



External Output Terminal (Top: optional Bottom: standard)



Cable Port (I.D.Φ50mm standard)



Shelf & Bracket Set



Optional items

Description	Product code
(1) Stainless steel punched metal shelf up to 15kg	211221
(2) Stainless steel wire shelf up to 20kg	212918
(3) External communication adapter	211880
(4) External alarm terminal	211881
(5) Time-up output terminal	211882
(6) Earthquake resistant fixture	211883

* (4) and (5) please specify when ordering main unit

External Communication Adapter is equipped with RS485-USB interchange adapter, 1m USB cable, 3m RS485 connection cable and utility software CD (accepts Windows XP, Vista, 7)

Dimensions (mm)

